

COMPRESSOR DEFINITION

Designation	NE U6214Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	269NA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	16.80	[cm ³] (1.025 cu.in)
2.1 Bore [mm]	31.190	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3AN3C-647	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	15(400)	[µF(VAC minimum)]
5 Motor protection	MST30APK-3261	
6 Start winding resistance	14.26	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.25	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	22.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.30	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5728	1443	1678	686	3.11	37.14	8.35	2.10	2.45

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2735	689	801	383	1.71	14.79	7.15	1.80	2.09
-10	(+14)	3444	868	1009	420	1.89	18.69	8.21	2.07	2.41
-5	(+23)	4308	1086	1262	462	2.09	23.47	9.32	2.35	2.73
0	(+32)	5329	1343	1562	510	2.31	29.16	10.44	2.63	3.06
+5	(+41)	6506	1640	1907	563	2.55	35.79	11.55	2.91	3.39
+10	(+50)	7839	1976	2297	621	2.81	43.40	12.63	3.18	3.70

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2455	619	719	407	1.82	14.34	6.03	1.52	1.77
-10	(+14)	3114	785	912	451	2.04	18.26	6.91	1.74	2.02
-5	(+23)	3911	986	1146	499	2.26	23.03	7.83	1.97	2.30
0	(+32)	4847	1221	1420	552	2.50	28.68	8.79	2.21	2.58
+5	(+41)	5922	1492	1735	608	2.76	35.24	9.74	2.46	2.86
+10	(+50)	7134	1798	2091	668	3.03	42.75	10.67	2.69	3.13

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2132	537	625	426	1.91	13.59	5.02	1.26	1.47
-10	(+14)	2730	688	800	480	2.16	17.46	5.68	1.43	1.67
-5	(+23)	3449	869	1011	537	2.43	22.15	6.41	1.62	1.88
0	(+32)	4289	1081	1257	597	2.70	27.70	7.18	1.81	2.10
+5	(+41)	5250	1323	1538	660	2.99	34.13	7.96	2.01	2.33
+10	(+50)	6331	1596	1855	726	3.30	41.47	8.72	2.20	2.56

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		