

COMPRESSOR DEFINITION

Designation	EM B66CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300446

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	10.61	[cm ³] (0.647 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8	[kg] (17.64 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V0.6	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(310)	[µF(VAC minimum)]
5 Motor protection	4TM232KFBYY-53	
6 Start winding resistance	12.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.60	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
648	163	190	102	0.50	2.03	6.38	1.61	1.87

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	355	89	104	68	0.36	1.11	5.27	1.33	1.54
-30	(-22)	471	119	138	78	0.40	1.48	6.10	1.54	1.79
-25	(-13)	627	158	184	89	0.45	1.97	7.05	1.78	2.06
-20	(- 4)	819	206	240	102	0.50	2.57	8.06	2.03	2.36
-15	(+ 5)	1044	263	306	115	0.56	3.29	9.10	2.29	2.67
-10	(+14)	1297	327	380	128	0.62	4.09	10.13	2.55	2.97

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	347	87	102	69	0.37	1.09	4.96	1.25	1.45
-30	(-22)	458	115	134	80	0.41	1.43	5.69	1.43	1.67
-25	(-13)	609	153	178	93	0.46	1.91	6.50	1.64	1.91
-20	(- 4)	796	201	233	108	0.53	2.50	7.38	1.86	2.16
-15	(+ 5)	1016	256	298	123	0.59	3.20	8.27	2.08	2.42
-10	(+14)	1265	319	371	139	0.66	3.99	9.15	2.31	2.68

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	303	76	89	69	0.37	0.95	4.40	1.11	1.29
-30	(-22)	409	103	120	81	0.41	1.28	5.04	1.27	1.48
-25	(-13)	554	140	162	96	0.47	1.74	5.77	1.45	1.69
-20	(- 4)	735	185	215	112	0.54	2.31	6.54	1.65	1.92
-15	(+ 5)	949	239	278	129	0.62	2.99	7.32	1.84	2.14
-10	(+14)	1192	300	349	148	0.70	3.76	8.08	2.04	2.37

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	276	70	81	70	0.37	0.86	3.95	1.00	1.16
-30	(-22)	374	94	109	83	0.42	1.17	4.55	1.15	1.33
-25	(-13)	511	129	150	98	0.49	1.61	5.22	1.31	1.53
-20	(- 4)	686	173	201	116	0.56	2.16	5.92	1.49	1.74
-15	(+ 5)	893	225	262	135	0.65	2.81	6.62	1.67	1.94
-10	(+14)	1129	284	331	155	0.74	3.56	7.29	1.84	2.14

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.2 +0.10/-0.05	[mm]	(0.165" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		