

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM E26CLT |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 711EA90 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 187 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 150 | [ml] (5.07 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO2 | |
| 4 Weight (with oil charge) | 8.1 | [kg] (17.86 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | TSD | |
| 2.1 Starting device | TSD2-220V/TSD2-220V1.2/TSD2-D-220V | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 2.5(350)/2(350)/3(350)/4(350) | [µF(VAC minimum)] |
| 5 Motor protection | CP4TMC112N61A5 | |
| 6 Start winding resistance | 22.65 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 40.45 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE LBP-NOFAN Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 273 | 69 | 80 | 42 | 0.19 | 0.86 | 6.58 | 1.66 | 1.93 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|---------------------------------------|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | ASHRAE32-NOFAN Static | | | | (Condensing temperature 35°C (+95°F)) | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 161 | 41 | 47 | 26 | 0.14 | 0.51 | 6.28 | 1.58 | 1.84 |
| -30 | (-22) | 225 | 57 | 66 | 31 | 0.15 | 0.70 | 7.20 | 1.81 | 2.11 |
| -25 | (-13) | 299 | 75 | 88 | 36 | 0.17 | 0.94 | 8.22 | 2.07 | 2.41 |
| -20 | (- 4) | 386 | 97 | 113 | 41 | 0.19 | 1.21 | 9.37 | 2.36 | 2.75 |
| -15 | (+ 5) | 489 | 123 | 143 | 46 | 0.21 | 1.54 | 10.68 | 2.69 | 3.13 |
| -10 | (+14) | 610 | 154 | 179 | 50 | 0.23 | 1.92 | 12.18 | 3.07 | 3.57 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | ASHRAE32-NOFAN Static | | | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 143 | 36 | 42 | 26 | 0.14 | 0.45 | 5.57 | 1.40 | 1.63 |
| -30 | (-22) | 204 | 52 | 60 | 32 | 0.16 | 0.64 | 6.41 | 1.62 | 1.88 |
| -25 | (-13) | 277 | 70 | 81 | 38 | 0.18 | 0.87 | 7.28 | 1.84 | 2.13 |
| -20 | (- 4) | 362 | 91 | 106 | 44 | 0.20 | 1.14 | 8.21 | 2.07 | 2.41 |
| -15 | (+ 5) | 462 | 116 | 135 | 50 | 0.23 | 1.46 | 9.22 | 2.32 | 2.70 |
| -10 | (+14) | 580 | 146 | 170 | 56 | 0.26 | 1.83 | 10.34 | 2.61 | 3.03 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | ASHRAE32-NOFAN Static | | | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 114 | 29 | 33 | 26 | 0.13 | 0.36 | 4.43 | 1.12 | 1.30 |
| -30 | (-22) | 175 | 44 | 51 | 32 | 0.15 | 0.55 | 5.38 | 1.36 | 1.58 |
| -25 | (-13) | 247 | 62 | 72 | 39 | 0.17 | 0.77 | 6.28 | 1.58 | 1.84 |
| -20 | (- 4) | 331 | 83 | 97 | 46 | 0.20 | 1.04 | 7.16 | 1.80 | 2.10 |
| -15 | (+ 5) | 429 | 108 | 126 | 53 | 0.24 | 1.35 | 8.05 | 2.03 | 2.36 |
| -10 | (+14) | 545 | 137 | 160 | 61 | 0.28 | 1.72 | 8.96 | 2.26 | 2.62 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|------------------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° up + 45° to Back | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted 0° up + 45° to Back | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 43° up + 45° to Back | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |