

COMPRESSOR DEFINITION

Designation	EM YS80HSP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513305060

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.76	[cm ³] (0.413 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	8.1	[kg] (17.86 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C3/8EA17E63/QPS2-A22MD3/QPS2-C22MD3J8	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(308)/5(310)	[µF(VAC minimum)]
5 Motor protection	4TM213PFBYY-53	
6 Start winding resistance	22.36	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.24	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	6.07	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.17	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.38	[A] - Measured according to UL 984
11 Approval boards certification	CE - IRAM - UKCA	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
692	174	203	117	0.57	3.93	5.93	1.49	1.74

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	348	88	102	71	0.36	1.97	4.89	1.23	1.43
-30 (-22)	510	128	149	87	0.44	2.89	5.87	1.48	1.72
-25 (-13)	711	179	208	103	0.52	4.04	6.91	1.74	2.02
-20 (- 4)	955	241	280	119	0.59	5.43	8.00	2.02	2.34
-15 (+ 5)	1245	314	365	136	0.67	7.11	9.15	2.31	2.68
-10 (+14)	1585	399	465	153	0.75	9.08	10.35	2.61	3.03

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	296	75	87	76	0.39	1.68	3.88	0.98	1.14
-30 (-22)	437	110	128	93	0.47	2.47	4.70	1.19	1.38
-25 (-13)	618	156	181	111	0.54	3.51	5.57	1.40	1.63
-20 (- 4)	843	212	247	130	0.62	4.80	6.49	1.63	1.90
-15 (+ 5)	1116	281	327	150	0.70	6.37	7.44	1.88	2.18
-10 (+14)	1441	363	422	171	0.79	8.25	8.44	2.13	2.47

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	231	58	68	83	0.41	1.31	2.79	0.70	0.82
-30 (-22)	350	88	103	100	0.48	1.98	3.54	0.89	1.04
-25 (-13)	511	129	150	119	0.56	2.90	4.32	1.09	1.27
-20 (- 4)	718	181	211	140	0.64	4.09	5.14	1.30	1.51
-15 (+ 5)	975	246	286	163	0.73	5.56	5.98	1.51	1.75
-10 (+14)	1284	323	376	187	0.84	7.35	6.85	1.73	2.01

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 30° up + 24° to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		