

COMPRESSOR DEFINITION

Designation	NE U6210GK
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	958IE71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	7.28	[cm ³] (0.444 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	13.200	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-70-31	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0590/J5	
6 Start winding resistance	6.83	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.15	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	39.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @127V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2343	590	687	486	6.16	25.25	4.82	1.21	1.41

E - PERFORMANCE - CURVES

TEST CONDITIONS: @127V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1788	450	524	358	5.82	15.09	4.98	1.25	1.46
-15	(+ 5)	2107	531	617	393	5.92	18.02	5.38	1.36	1.58
-10	(+14)	2623	661	769	424	6.04	22.70	6.20	1.56	1.82
-5	(+23)	3337	841	978	451	6.17	29.28	7.40	1.87	2.17
0	(+32)	4247	1070	1244	473	6.31	37.93	8.97	2.26	2.63
+5	(+41)	5354	1349	1569	492	6.47	48.80	10.88	2.74	3.19
+10	(+50)	6657	1678	1951	507	6.65	62.05	13.11	3.30	3.84

TEST CONDITIONS: @127V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1454	366	426	373	5.86	14.19	3.90	0.98	1.14
-15	(+ 5)	1730	436	507	412	5.98	17.10	4.21	1.06	1.23
-10	(+14)	2163	545	634	447	6.12	21.66	4.83	1.22	1.41
-5	(+23)	2753	694	807	479	6.28	28.04	5.73	1.44	1.68
0	(+32)	3498	882	1025	506	6.45	36.39	6.91	1.74	2.02
+5	(+41)	4400	1109	1289	530	6.64	46.86	8.32	2.10	2.44
+10	(+50)	5457	1375	1599	549	6.85	59.62	9.95	2.51	2.92

TEST CONDITIONS: @127V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1098	277	322	388	5.89	12.93	2.83	0.71	0.83
-15	(+ 5)	1333	336	391	435	6.04	15.87	3.07	0.77	0.90
-10	(+14)	1684	424	493	477	6.21	20.37	3.53	0.89	1.03
-5	(+23)	2150	542	630	515	6.41	26.59	4.17	1.05	1.22
0	(+32)	2732	688	800	549	6.62	34.68	4.98	1.25	1.46
+5	(+41)	3429	864	1005	579	6.85	44.82	5.93	1.49	1.74
+10	(+50)	4242	1069	1243	605	7.10	57.14	7.00	1.76	2.05

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		