

COMPRESSOR DEFINITION

Designation	EM 2U60HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513305545

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.54	[cm ³] (0.338 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.23	[kg] (15.94 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M4R7MC1/8EA14C1/8EA14E61/8EA14E62/8EA14E63/8M4R7	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	CP4TMC431K61	
6 Start winding resistance	6.93	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.08	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.32	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.94	[A] - Measured according to UL 984
11 Approval boards certification	IMTRO - TUV	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @127V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
631	159	185	126	1.59	3.59	5.01	1.26	1.47

E - PERFORMANCE - CURVES

TEST CONDITIONS: @127V60Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	373	94	109	82	1.34	2.11	4.53	1.14	1.33
-30 (-22)	494	125	145	97	1.41	2.80	5.18	1.30	1.52
-25 (-13)	660	166	193	111	1.47	3.75	6.01	1.52	1.76
-20 (- 4)	871	220	255	124	1.53	4.96	7.00	1.76	2.05
-15 (+ 5)	1129	285	331	138	1.60	6.45	8.11	2.04	2.38
-10 (+14)	1435	362	421	153	1.69	8.22	9.30	2.34	2.72

TEST CONDITIONS: @127V60Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	312	79	91	84	1.36	1.77	3.70	0.93	1.08
-30 (-22)	444	112	130	101	1.45	2.52	4.44	1.12	1.30
-25 (-13)	614	155	180	117	1.52	3.49	5.28	1.33	1.55
-20 (- 4)	823	207	241	132	1.59	4.68	6.20	1.56	1.82
-15 (+ 5)	1072	270	314	149	1.68	6.12	7.17	1.81	2.10
-10 (+14)	1362	343	399	167	1.78	7.81	8.15	2.05	2.39

TEST CONDITIONS: @127V60Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	244	61	71	84	1.33	1.38	2.90	0.73	0.85
-30 (-22)	386	97	113	102	1.44	2.19	3.76	0.95	1.10
-25 (-13)	560	141	164	120	1.54	3.18	4.65	1.17	1.36
-20 (- 4)	766	193	225	138	1.63	4.36	5.54	1.40	1.62
-15 (+ 5)	1006	254	295	157	1.73	5.74	6.40	1.61	1.88
-10 (+14)	1282	323	376	178	1.86	7.34	7.20	1.81	2.11

E - PERFORMANCE - CURVES

TEST CONDITIONS: @127V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	167	42	49	81	1.25	0.95	2.07	0.52	0.61
-30	(-22)	320	81	94	101	1.39	1.82	3.08	0.78	0.90
-25	(-13)	498	125	146	121	1.51	2.83	4.06	1.02	1.19
-20	(- 4)	702	177	206	142	1.63	3.99	4.95	1.25	1.45
-15	(+ 5)	933	235	273	164	1.76	5.32	5.74	1.45	1.68
-10	(+14)	1193	301	350	188	1.91	6.83	6.39	1.61	1.87

F - EXTERNAL CHARACTERISTICS

1 Base plate	New Base Plate EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 30° up + 24° to Back		
3.3 PROCESS	6.35 +0.08/-0.08	[mm]	(0.250" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		