

COMPRESSOR DEFINITION

Designation	EG ZS80HLC
Nominal Voltage/Frequency	220-240 V 50-60 Hz
Engineering Number	513701124

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50-60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.36	[cm ³] (0.388 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	230	[ml] (7.78 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.28	[kg] (24.87 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C1/QPS2-A22MG1/QPS2-A22MG1 092	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM283KFBYY-53	
6 Start winding resistance	22.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.00	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	7.60	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.15	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.50	[A] - Measured according to UL 984
11 Approval boards certification	CE - IMTRO - IRAM - NOM - TUV - UKCA	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
651	164	191	119	0.86	3.70	5.48	1.38	1.61

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	324	82	95	76	0.73	1.83	4.27	1.08	1.25
-30 (-22)	488	123	143	94	0.79	2.77	5.17	1.30	1.51
-25 (-13)	667	168	195	112	0.85	3.79	5.98	1.51	1.75
-20 (- 4)	871	219	255	129	0.91	4.96	6.78	1.71	1.99
-15 (+ 5)	1107	279	324	146	0.97	6.32	7.62	1.92	2.23
-10 (+14)	1386	349	406	162	1.03	7.94	8.57	2.16	2.51

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	262	66	77	67	0.70	1.48	3.91	0.98	1.14
-30 (-22)	419	106	123	88	0.77	2.38	4.70	1.18	1.38
-25 (-13)	596	150	175	110	0.85	3.38	5.40	1.36	1.58
-20 (- 4)	801	202	235	132	0.93	4.56	6.05	1.52	1.77
-15 (+ 5)	1044	263	306	155	1.01	5.96	6.73	1.70	1.97
-10 (+14)	1332	336	390	178	1.09	7.63	7.49	1.89	2.20

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	201	51	59	61	0.68	1.14	3.31	0.83	0.97
-30 (-22)	345	87	101	84	0.76	1.96	4.09	1.03	1.20
-25 (-13)	513	129	150	108	0.84	2.91	4.75	1.20	1.39
-20 (- 4)	714	180	209	134	0.93	4.06	5.35	1.35	1.57
-15 (+ 5)	957	241	280	160	1.02	5.46	5.95	1.50	1.74
-10 (+14)	1250	315	366	188	1.12	7.16	6.62	1.67	1.94

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		