

### COMPRESSOR DEFINITION

Designation	NE U6214Z
Nominal Voltage/Frequency	200-230 V 50 Hz / 208-230 V 60 Hz
Engineering Number	269NB71

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	200-230 / 50	[ V / Hz ]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak (gauge)	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	16.80	[cm <sup>3</sup> ] (1.025 cu.in)
2.1 Bore [mm]	31.190	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.48	[kg] (25.31 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-230 V 50 Hz / 208-230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AL3C-649	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	12.5(400)	[µF(VAC minimum)]
5 Motor protection	MSP00LJ-3261	
6 Start winding resistance	9.21	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.16	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	25.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@208V60Hz</b>			<b>ASHRAEHBP46</b> <b>Fan</b>		Evaporating temperature (Condensing temperature		<b>7.2°C (44.96°F)</b> <b>54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6478	1632	1898	842	4.10	42.00	7.69	1.94	2.25

### E - PERFORMANCE - CURVES

TEST CONDITIONS: <b>@208V60Hz</b>			<b>ASHRAE46</b> <b>Fan</b>		(Condensing temperature <b>35°C (+95°F)</b> )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	3162	797	927	426	2.03	17.10	7.43	1.87	2.18
-10	(+14)	4010	1011	1175	479	2.28	21.76	8.37	2.11	2.45
-5	(+23)	4993	1258	1463	542	2.59	27.20	9.20	2.32	2.70
0	(+32)	6109	1539	1790	617	2.95	33.43	9.90	2.49	2.90
+5	(+41)	7360	1855	2157	703	3.38	40.49	10.48	2.64	3.07
+10	(+50)	8745	2204	2562	800	3.86	48.41	10.93	2.76	3.20

TEST CONDITIONS: <b>@208V60Hz</b>			<b>ASHRAE46</b> <b>Fan</b>		(Condensing temperature <b>45°C (+113°F)</b> )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2825	712	828	452	2.16	16.51	6.25	1.57	1.83
-10	(+14)	3586	904	1051	512	2.45	21.03	7.01	1.77	2.05
-5	(+23)	4476	1128	1311	581	2.79	26.35	7.71	1.94	2.26
0	(+32)	5495	1385	1610	660	3.17	32.51	8.32	2.10	2.44
+5	(+41)	6644	1674	1947	749	3.61	39.54	8.87	2.23	2.60
+10	(+50)	7923	1997	2322	848	4.10	47.49	9.34	2.35	2.74

TEST CONDITIONS: <b>@208V60Hz</b>			<b>ASHRAE46</b> <b>Fan</b>		(Condensing temperature <b>55°C (+131°F)</b> )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2464	621	722	472	2.26	15.69	5.21	1.31	1.53
-10	(+14)	3131	789	918	543	2.61	20.03	5.77	1.45	1.69
-5	(+23)	3924	989	1150	622	3.00	25.21	6.31	1.59	1.85
0	(+32)	4842	1220	1419	709	3.42	31.28	6.82	1.72	2.00
+5	(+41)	5885	1483	1724	805	3.89	38.26	7.30	1.84	2.14
+10	(+50)	7053	1777	2067	909	4.40	46.19	7.76	1.96	2.28

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		