

COMPRESSOR DEFINITION

| | |
|---------------------------|--------------------|
| Designation | EG AS100HLR |
| Nominal Voltage/Frequency | 220-240 V 50-60 Hz |
| Engineering Number | 513701309 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|--------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 220-240 / 50-60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-CSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static/Fan | 198 to 255 V | 198 to 255 V |
| 8.2 LBP (43°C Ambient temperature) | Static/Fan | 198 to 255 V | 198 to 255 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 14.2 | [kgf/cm ²] (202 psig) | / °C - °F |
| 9.2 Peak | 15.9 | [kgf/cm ²] (226 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/3 | [hp] |
| 2 Displacement | 7.95 | [cm ³] (0.485 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 230 | [ml] (7.78 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 10.47 | [kg] (23.08 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|---------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50-60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | Current Relay | |
| 2.1 Starting device | 213516442/213516469 | |
| 3 Start capacitor | 88-108(180) | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | DRB210L61A*F | |
| 6 Start winding resistance | 34.00 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 8.80 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50/60 Hz) | 17.55/16.64 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50/60 Hz) | - | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50/60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CCC - CE - IRAM - UKCA - UL - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|--|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| 852 | 215 | 250 | 167 | 1.36 | 4.84 | 5.09 | 1.28 | 1.49 | |

| | | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|--|
| TEST CONDITIONS: @220V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] | |
| 1057 | 266 | 310 | 193 | 1.25 | 6.01 | 5.49 | 1.38 | 1.61 | |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 442 | 111 | 129 | 110 | 0.94 | 2.50 | 3.99 | 1.01 | 1.17 |
| -30 (-22) | 620 | 156 | 182 | 130 | 1.10 | 3.52 | 4.78 | 1.20 | 1.40 |
| -25 (-13) | 828 | 209 | 243 | 151 | 1.26 | 4.70 | 5.52 | 1.39 | 1.62 |
| -20 (- 4) | 1074 | 271 | 315 | 172 | 1.42 | 6.11 | 6.25 | 1.58 | 1.83 |
| -15 (+ 5) | 1369 | 345 | 401 | 194 | 1.59 | 7.82 | 7.02 | 1.77 | 2.06 |
| -10 (+14) | 1724 | 434 | 505 | 218 | 1.79 | 9.88 | 7.85 | 1.98 | 2.30 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 362 | 91 | 106 | 106 | 0.90 | 2.05 | 3.42 | 0.86 | 1.00 |
| -30 (-22) | 554 | 140 | 162 | 131 | 1.10 | 3.14 | 4.23 | 1.07 | 1.24 |
| -25 (-13) | 769 | 194 | 225 | 156 | 1.29 | 4.36 | 4.94 | 1.25 | 1.45 |
| -20 (- 4) | 1016 | 256 | 298 | 182 | 1.49 | 5.78 | 5.60 | 1.41 | 1.64 |
| -15 (+ 5) | 1306 | 329 | 383 | 209 | 1.70 | 7.45 | 6.25 | 1.58 | 1.83 |
| -10 (+14) | 1649 | 415 | 483 | 237 | 1.94 | 9.44 | 6.94 | 1.75 | 2.03 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @220V50Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|--|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 263 | 66 | 77 | 89 | 0.78 | 1.49 | 2.95 | 0.74 | 0.87 |
| -30 | (-22) | 471 | 119 | 138 | 122 | 1.04 | 2.67 | 3.77 | 0.95 | 1.10 |
| -25 | (-13) | 695 | 175 | 204 | 155 | 1.30 | 3.94 | 4.45 | 1.12 | 1.30 |
| -20 | (- 4) | 945 | 238 | 277 | 188 | 1.56 | 5.38 | 5.04 | 1.27 | 1.48 |
| -15 | (+ 5) | 1231 | 310 | 361 | 222 | 1.83 | 7.03 | 5.58 | 1.41 | 1.64 |
| -10 | (+14) | 1564 | 394 | 458 | 257 | 2.11 | 8.96 | 6.11 | 1.54 | 1.79 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 45°C (+113°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|--|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 543 | 137 | 159 | 129 | 0.86 | 3.07 | 4.18 | 1.05 | 1.23 |
| -30 | (-22) | 762 | 192 | 223 | 153 | 1.01 | 4.32 | 5.01 | 1.26 | 1.47 |
| -25 | (-13) | 1017 | 256 | 298 | 177 | 1.15 | 5.77 | 5.79 | 1.46 | 1.70 |
| -20 | (- 4) | 1319 | 332 | 387 | 201 | 1.30 | 7.51 | 6.55 | 1.65 | 1.92 |
| -15 | (+ 5) | 1682 | 424 | 493 | 228 | 1.46 | 9.60 | 7.35 | 1.85 | 2.15 |
| -10 | (+14) | 2117 | 534 | 620 | 256 | 1.64 | 12.13 | 8.23 | 2.07 | 2.41 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 55°C (+131°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|--|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 445 | 112 | 130 | 124 | 0.83 | 2.52 | 3.59 | 0.90 | 1.05 |
| -30 | (-22) | 681 | 172 | 200 | 153 | 1.01 | 3.86 | 4.43 | 1.12 | 1.30 |
| -25 | (-13) | 945 | 238 | 277 | 183 | 1.19 | 5.36 | 5.18 | 1.31 | 1.52 |
| -20 | (- 4) | 1248 | 314 | 366 | 213 | 1.38 | 7.10 | 5.87 | 1.48 | 1.72 |
| -15 | (+ 5) | 1604 | 404 | 470 | 245 | 1.58 | 9.15 | 6.55 | 1.65 | 1.92 |
| -10 | (+14) | 2024 | 510 | 593 | 278 | 1.79 | 11.60 | 7.27 | 1.83 | 2.13 |

| TEST CONDITIONS: @220V60Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|----------------------------|--------------------|---------|-----------------------------|--|-------------------------|---------------------------|------|------|------|
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | | |
| | °C | (°F) | [Btu/h] | | | | [kcal/h] | [W] | [W] | [A] |
| -35 | (-31) | 323 | 81 | 95 | 105 | 0.72 | 1.83 | 3.09 | 0.78 | 0.91 |
| -30 | (-22) | 578 | 146 | 170 | 143 | 0.96 | 3.28 | 3.95 | 1.00 | 1.16 |
| -25 | (-13) | 854 | 215 | 250 | 181 | 1.19 | 4.85 | 4.67 | 1.18 | 1.37 |
| -20 | (- 4) | 1160 | 292 | 340 | 220 | 1.43 | 6.60 | 5.28 | 1.33 | 1.55 |
| -15 | (+ 5) | 1512 | 381 | 443 | 260 | 1.68 | 8.63 | 5.85 | 1.47 | 1.71 |
| -10 | (+14) | 1921 | 484 | 563 | 301 | 1.94 | 11.00 | 6.40 | 1.61 | 1.87 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|---------------------------------------|------|--------------------------|
| 1 Base plate | European Standard EG/F/AMEM Version 2 | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted | | |
| 3.2 DISCHARGE | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |