

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM Y26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 875HA98 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.45 | [kg] (16.42 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | MI2021 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | 2.5(440) | [μF(VAC minimum)] |
| 5 Motor protection | AX23AHY | |
| 6 Start winding resistance | 25.20 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 54.50 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 282 | 71 | 83 | 53 | 0.25 | 0.89 | 5.32 | 1.34 | 1.56 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 151 | 38 | 44 | 37 | 0.19 | 0.47 | 4.09 | 1.03 | 1.20 |
| -30 | (-22) | 209 | 53 | 61 | 43 | 0.21 | 0.65 | 4.86 | 1.22 | 1.42 |
| -25 | (-13) | 280 | 71 | 82 | 50 | 0.24 | 0.88 | 5.65 | 1.42 | 1.66 |
| -20 | (- 4) | 366 | 92 | 107 | 56 | 0.27 | 1.15 | 6.49 | 1.64 | 1.90 |
| -15 | (+ 5) | 467 | 118 | 137 | 63 | 0.30 | 1.47 | 7.41 | 1.87 | 2.17 |
| -10 | (+14) | 584 | 147 | 171 | 70 | 0.33 | 1.84 | 8.41 | 2.12 | 2.46 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 134 | 34 | 39 | 38 | 0.19 | 0.42 | 3.56 | 0.90 | 1.04 |
| -30 | (-22) | 188 | 47 | 55 | 43 | 0.22 | 0.59 | 4.33 | 1.09 | 1.27 |
| -25 | (-13) | 256 | 65 | 75 | 51 | 0.25 | 0.80 | 5.07 | 1.28 | 1.49 |
| -20 | (- 4) | 340 | 86 | 100 | 59 | 0.28 | 1.07 | 5.79 | 1.46 | 1.70 |
| -15 | (+ 5) | 440 | 111 | 129 | 67 | 0.32 | 1.38 | 6.52 | 1.64 | 1.91 |
| -10 | (+14) | 555 | 140 | 163 | 76 | 0.36 | 1.75 | 7.29 | 1.84 | 2.14 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 107 | 27 | 31 | 39 | 0.20 | 0.34 | 2.76 | 0.70 | 0.81 |
| -30 | (-22) | 161 | 41 | 47 | 44 | 0.22 | 0.51 | 3.66 | 0.92 | 1.07 |
| -25 | (-13) | 231 | 58 | 68 | 52 | 0.25 | 0.72 | 4.45 | 1.12 | 1.30 |
| -20 | (- 4) | 316 | 80 | 93 | 61 | 0.29 | 0.99 | 5.17 | 1.30 | 1.52 |
| -15 | (+ 5) | 418 | 105 | 122 | 72 | 0.34 | 1.32 | 5.84 | 1.47 | 1.71 |
| -10 | (+14) | 537 | 135 | 157 | 83 | 0.39 | 1.69 | 6.48 | 1.63 | 1.90 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.2.1 Material | Copper(OD) | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |