

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM Y26CLC |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 875HA98 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 5.19 | [cm ³] (0.317 cu.in) |
| 2.1 Bore [mm] | 21.000 | |
| 2.2 Stroke [mm] | 15.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.45 | [kg] (16.42 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | MI2021 | |
| 3 Start capacitor | - | [μF(VAC minimum)] |
| 4 Run capacitor | - | [μF(VAC minimum)] |
| 5 Motor protection | AX23AHY | |
| 6 Start winding resistance | 25.20 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 54.50 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | - | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | - | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 282 | 71 | 83 | 55 | 0.36 | 0.89 | 5.13 | 1.29 | 1.50 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 151 | 38 | 44 | 39 | 0.31 | 0.47 | 3.93 | 0.99 | 1.15 |
| -30 | (-22) | 212 | 53 | 62 | 45 | 0.32 | 0.66 | 4.67 | 1.18 | 1.37 |
| -25 | (-13) | 282 | 71 | 83 | 52 | 0.35 | 0.89 | 5.41 | 1.36 | 1.58 |
| -20 | (- 4) | 365 | 92 | 107 | 59 | 0.37 | 1.15 | 6.16 | 1.55 | 1.81 |
| -15 | (+ 5) | 462 | 117 | 136 | 66 | 0.40 | 1.46 | 6.97 | 1.76 | 2.04 |
| -10 | (+14) | 577 | 145 | 169 | 73 | 0.42 | 1.82 | 7.88 | 1.99 | 2.31 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 132 | 33 | 39 | 39 | 0.31 | 0.41 | 3.39 | 0.85 | 0.99 |
| -30 | (-22) | 190 | 48 | 56 | 46 | 0.33 | 0.59 | 4.13 | 1.04 | 1.21 |
| -25 | (-13) | 257 | 65 | 75 | 54 | 0.35 | 0.81 | 4.81 | 1.21 | 1.41 |
| -20 | (- 4) | 338 | 85 | 99 | 62 | 0.38 | 1.06 | 5.44 | 1.37 | 1.59 |
| -15 | (+ 5) | 433 | 109 | 127 | 71 | 0.42 | 1.36 | 6.08 | 1.53 | 1.78 |
| -10 | (+14) | 546 | 138 | 160 | 81 | 0.45 | 1.72 | 6.75 | 1.70 | 1.98 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|--------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 104 | 26 | 30 | 38 | 0.30 | 0.32 | 2.74 | 0.69 | 0.80 |
| -30 | (-22) | 162 | 41 | 48 | 45 | 0.32 | 0.51 | 3.56 | 0.90 | 1.04 |
| -25 | (-13) | 231 | 58 | 68 | 54 | 0.35 | 0.73 | 4.25 | 1.07 | 1.25 |
| -20 | (- 4) | 314 | 79 | 92 | 65 | 0.39 | 0.99 | 4.85 | 1.22 | 1.42 |
| -15 | (+ 5) | 411 | 104 | 120 | 77 | 0.44 | 1.30 | 5.38 | 1.36 | 1.58 |
| -10 | (+14) | 526 | 133 | 154 | 89 | 0.49 | 1.66 | 5.89 | 1.49 | 1.73 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.2.1 Material | Copper(OD) | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |