

### COMPRESSOR DEFINITION

Designation	VES A9C
Nominal Voltage/Frequency	230 V 40-150 Hz
Engineering Number	800MY47

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	230 / 40-150	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 254 V	187 to 254 V
8.2 LBP (43°C Ambient temperature)	Static	187 to 254 V	187 to 254 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	9.04	[cm <sup>3</sup> ] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	200	[ml] (6.76 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	6	[kg] (13.23 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 40-150 Hz 3~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	VES 2456 XX X X	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	INVERTER VES 2456X	
6 Start winding resistance	11.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	11.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (40/150 Hz)	2.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (40/150 Hz)	2.10	[A]
10 FLA - Full Load Amperage HBP (40/150 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@220V1300RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
168	42	49	36	0.30	0.64	4.71	1.19	1.38

TEST CONDITIONS: <b>@220V1600RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
209	53	61	42	0.35	0.80	4.95	1.25	1.45

TEST CONDITIONS: <b>@220V2000RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
264	67	77	53	0.43	1.01	5.02	1.27	1.47

TEST CONDITIONS: <b>@220V3000RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
404	102	118	81	0.62	1.54	5.01	1.26	1.47

TEST CONDITIONS: <b>@220V4500RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
573	144	168	124	0.95	2.18	4.61	1.16	1.35

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V1300RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	134	34	39	24	0.21	0.43	5.67	1.43	1.66	
-30 (-22)	178	45	52	27	0.24	0.57	6.53	1.64	1.91	
-25 (-13)	232	59	68	31	0.28	0.75	7.36	1.85	2.16	
-20 (- 4)	300	76	88	36	0.32	0.96	8.26	2.08	2.42	
-15 (+ 5)	381	96	112	41	0.35	1.23	9.34	2.35	2.74	
-10 (+14)	478	120	140	45	0.38	1.54	10.69	2.69	3.13	

TEST CONDITIONS: @220V1300RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	111	28	32	23	0.21	0.38	4.81	1.21	1.41	
-30 (-22)	153	39	45	28	0.25	0.53	5.40	1.36	1.58	
-25 (-13)	206	52	60	35	0.29	0.72	5.93	1.49	1.74	
-20 (- 4)	270	68	79	41	0.34	0.94	6.47	1.63	1.90	
-15 (+ 5)	346	87	102	48	0.39	1.21	7.13	1.80	2.09	
-10 (+14)	437	110	128	54	0.44	1.53	8.01	2.02	2.35	

TEST CONDITIONS: @220V1300RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	91	23	27	24	0.21	0.35	3.73	0.94	1.09	
-30 (-22)	126	32	37	29	0.25	0.48	4.28	1.08	1.25	
-25 (-13)	169	43	49	36	0.30	0.64	4.70	1.19	1.38	
-20 (- 4)	222	56	65	44	0.37	0.85	5.10	1.29	1.49	
-15 (+ 5)	287	72	84	52	0.44	1.10	5.56	1.40	1.63	
-10 (+14)	364	92	107	59	0.52	1.40	6.19	1.56	1.81	

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	157	40	46	28	0.24	0.50	5.72	1.44	1.68	
-30 (-22)	212	53	62	33	0.28	0.68	6.53	1.64	1.91	
-25 (-13)	281	71	82	38	0.32	0.90	7.41	1.87	2.17	
-20 (- 4)	365	92	107	43	0.36	1.17	8.41	2.12	2.47	
-15 (+ 5)	468	118	137	49	0.40	1.51	9.59	2.42	2.81	
-10 (+14)	590	149	173	54	0.44	1.90	10.99	2.77	3.22	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	144	36	42	29	0.26	0.50	4.94	1.24	1.45
-30	(-22)	191	48	56	35	0.30	0.67	5.53	1.39	1.62
-25	(-13)	250	63	73	41	0.34	0.87	6.12	1.54	1.79
-20	(- 4)	324	82	95	48	0.39	1.13	6.75	1.70	1.98
-15	(+ 5)	412	104	121	55	0.44	1.44	7.47	1.88	2.19
-10	(+14)	519	131	152	62	0.49	1.82	8.34	2.10	2.44

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	110	28	32	29	0.24	0.42	3.83	0.96	1.12
-30	(-22)	154	39	45	35	0.30	0.59	4.43	1.12	1.30
-25	(-13)	209	53	61	42	0.35	0.80	4.95	1.25	1.45
-20	(- 4)	275	69	81	51	0.42	1.05	5.43	1.37	1.59
-15	(+ 5)	356	90	104	60	0.48	1.36	5.93	1.49	1.74
-10	(+14)	451	114	132	69	0.55	1.73	6.49	1.64	1.90

TEST CONDITIONS: @220V2000RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	201	51	59	35	0.30	0.64	5.74	1.45	1.68
-30	(-22)	275	69	81	41	0.34	0.88	6.61	1.67	1.94
-25	(-13)	365	92	107	48	0.38	1.17	7.53	1.90	2.21
-20	(- 4)	471	119	138	55	0.43	1.51	8.55	2.15	2.50
-15	(+ 5)	596	150	175	62	0.49	1.92	9.68	2.44	2.84
-10	(+14)	741	187	217	68	0.54	2.39	10.97	2.76	3.21

TEST CONDITIONS: @220V2000RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	173	44	51	36	0.29	0.60	4.85	1.22	1.42
-30	(-22)	238	60	70	43	0.35	0.83	5.50	1.39	1.61
-25	(-13)	318	80	93	51	0.41	1.11	6.17	1.56	1.81
-20	(- 4)	414	104	121	60	0.47	1.44	6.89	1.74	2.02
-15	(+ 5)	528	133	155	68	0.54	1.84	7.68	1.94	2.25
-10	(+14)	663	167	194	77	0.61	2.32	8.58	2.16	2.51

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		CECOMAF			(Condensing temperature 55°C (+131°F))					
@220V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	143	36	42	36	0.29	0.54	3.97	1.00	1.16	
-30 (-22)	197	50	58	44	0.36	0.75	4.51	1.14	1.32	
-25 (-13)	264	67	77	53	0.43	1.01	5.03	1.27	1.47	
-20 (- 4)	348	88	102	63	0.50	1.33	5.54	1.40	1.62	
-15 (+ 5)	450	113	132	74	0.58	1.72	6.09	1.53	1.78	
-10 (+14)	573	144	168	85	0.66	2.20	6.70	1.69	1.96	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 35°C (+95°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	312	79	91	54	0.42	1.00	5.83	1.47	1.71	
-30 (-22)	422	106	124	64	0.49	1.35	6.62	1.67	1.94	
-25 (-13)	556	140	163	75	0.57	1.78	7.44	1.88	2.18	
-20 (- 4)	716	180	210	86	0.66	2.30	8.32	2.10	2.44	
-15 (+ 5)	907	228	266	98	0.75	2.92	9.28	2.34	2.72	
-10 (+14)	1131	285	331	109	0.84	3.65	10.35	2.61	3.03	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 45°C (+113°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	263	66	77	54	0.43	0.91	4.83	1.22	1.42	
-30 (-22)	360	91	105	66	0.51	1.25	5.46	1.38	1.60	
-25 (-13)	478	120	140	78	0.61	1.66	6.09	1.53	1.78	
-20 (- 4)	622	157	182	92	0.71	2.17	6.75	1.70	1.98	
-15 (+ 5)	795	200	233	106	0.81	2.77	7.48	1.89	2.19	
-10 (+14)	999	252	293	120	0.92	3.50	8.30	2.09	2.43	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 55°C (+131°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	218	55	64	55	0.43	0.83	3.99	1.01	1.17	
-30 (-22)	301	76	88	67	0.52	1.15	4.51	1.14	1.32	
-25 (-13)	404	102	118	81	0.62	1.54	5.01	1.26	1.47	
-20 (- 4)	531	134	156	96	0.74	2.03	5.52	1.39	1.62	
-15 (+ 5)	685	173	201	113	0.86	2.62	6.07	1.53	1.78	
-10 (+14)	869	219	255	130	0.98	3.34	6.69	1.69	1.96	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	463	117	136	87	0.66	1.48	5.35	1.35	1.57
-30	(-22)	603	152	177	100	0.75	1.94	6.01	1.52	1.76
-25	(-13)	774	195	227	115	0.86	2.49	6.71	1.69	1.97
-20	(- 4)	984	248	288	132	1.00	3.16	7.46	1.88	2.19
-15	(+ 5)	1240	313	363	150	1.14	3.99	8.26	2.08	2.42
-10	(+14)	1552	391	455	170	1.27	5.00	9.15	2.31	2.68

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	400	101	117	89	0.70	1.39	4.46	1.12	1.31
-30	(-22)	524	132	154	105	0.80	1.82	5.00	1.26	1.47
-25	(-13)	676	170	198	122	0.92	2.35	5.57	1.40	1.63
-20	(- 4)	862	217	253	140	1.06	3.01	6.18	1.56	1.81
-15	(+ 5)	1092	275	320	160	1.20	3.81	6.86	1.73	2.01
-10	(+14)	1373	346	402	180	1.32	4.81	7.62	1.92	2.23

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	317	80	93	86	0.67	1.21	3.68	0.93	1.08
-30	(-22)	433	109	127	104	0.80	1.65	4.13	1.04	1.21
-25	(-13)	573	145	168	124	0.94	2.18	4.61	1.16	1.35
-20	(- 4)	745	188	218	145	1.10	2.85	5.15	1.30	1.51
-15	(+ 5)	957	241	280	167	1.24	3.67	5.74	1.45	1.68
-10	(+14)	1216	306	356	189	1.36	4.67	6.42	1.62	1.88

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 5° out + 63° up		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 47° up + 59° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		