

### COMPRESSOR DEFINITION

Designation	<b>VEM T6H</b>
Nominal Voltage/Frequency	<b>230 V 53-150 Hz</b>
Engineering Number	<b>513903025</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	230 / 53-150	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	103 to 140 V	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	103 to 140 V	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	5.72	[cm <sup>3</sup> ] (0.349 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.400	
3 Lubricant charge	220	[ml] (7.44 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.99	[kg] (17.61 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 53-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	VCC31156XXXX	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	VCC31156XXXXX	
6 Start winding resistance	22.58	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	22.58	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (53/150 Hz)	2.10/2.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (53/150 Hz)	2.10/2.10	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (53/150 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMTRO - TUV - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@115V1600RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	67	1.13	1.88	4.92	1.24	1.44

TEST CONDITIONS: <b>@115V2000RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
380	96	111	75	1.24	2.16	5.09	1.28	1.49

TEST CONDITIONS: <b>@115V3000RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
585	147	171	111	1.77	3.32	5.28	1.33	1.55

TEST CONDITIONS: <b>@115V4500RPM</b>			<b>ASHRAELBP32</b> <b>Static</b>		Evaporating temperature (Condensing temperature	<b>-23.3°C (-9.94°F)</b> <b>54.4°C (129.92°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
780	197	229	154	2.37	4.43	5.06	1.28	1.48

### E - PERFORMANCE - CURVES

TEST CONDITIONS: <b>@115V2000RPM</b>		<b>ASHRAE32</b> <b>Static</b>				(Condensing temperature <b>35°C (+95°F)</b> )			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
°C (°F)									
-35 (-31)	234	59	69	44	0.80	1.32	5.33	1.34	1.56
-30 (-22)	314	79	92	52	0.95	1.78	6.07	1.53	1.78
-25 (-13)	414	104	121	60	1.11	2.35	6.91	1.74	2.02
-20 (- 4)	536	135	157	69	1.27	3.05	7.85	1.98	2.30
-15 (+ 5)	683	172	200	77	1.42	3.90	8.90	2.24	2.61
-10 (+14)	858	216	252	85	1.56	4.92	10.07	2.54	2.95

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 45°C (+113°F))					
@115V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	209	53	61	46	0.82	1.18	4.51	1.14	1.32	
-30 (-22)	287	72	84	55	0.97	1.63	5.17	1.30	1.51	
-25 (-13)	384	97	113	65	1.15	2.18	5.87	1.48	1.72	
-20 (- 4)	503	127	147	75	1.34	2.86	6.63	1.67	1.94	
-15 (+ 5)	646	163	189	86	1.54	3.69	7.45	1.88	2.18	
-10 (+14)	817	206	239	98	1.73	4.68	8.34	2.10	2.44	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 55°C (+131°F))					
@115V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	181	46	53	48	0.86	1.02	3.80	0.96	1.11	
-30 (-22)	257	65	75	58	1.02	1.45	4.43	1.12	1.30	
-25 (-13)	350	88	103	69	1.22	1.99	5.06	1.28	1.48	
-20 (- 4)	466	117	136	81	1.44	2.65	5.70	1.44	1.67	
-15 (+ 5)	605	152	177	95	1.67	3.45	6.35	1.60	1.86	
-10 (+14)	772	194	226	110	1.91	4.42	7.02	1.77	2.06	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 65°C (+149°F))					
@115V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	150	38	44	48	0.93	0.85	3.09	0.78	0.90	
-30 (-22)	223	56	65	59	1.09	1.26	3.76	0.95	1.10	
-25 (-13)	314	79	92	72	1.30	1.78	4.37	1.10	1.28	
-20 (- 4)	425	107	125	86	1.54	2.42	4.94	1.25	1.45	
-15 (+ 5)	560	141	164	103	1.81	3.20	5.48	1.38	1.61	
-10 (+14)	722	182	212	121	2.10	4.14	5.99	1.51	1.76	

TEST CONDITIONS:		ASHRAE32			(Condensing temperature 35°C (+95°F))					
@115V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%			+/- 5%	+/- 5%	+/- 5%	+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	359	90	105	67	1.19	2.03	5.31	1.34	1.56	
-30 (-22)	473	119	139	82	1.42	2.68	5.80	1.46	1.70	
-25 (-13)	620	156	182	96	1.65	3.52	6.52	1.64	1.91	
-20 (- 4)	805	203	236	109	1.88	4.58	7.42	1.87	2.17	
-15 (+ 5)	1029	259	301	122	2.11	5.87	8.45	2.13	2.48	
-10 (+14)	1296	326	380	135	2.33	7.42	9.57	2.41	2.81	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V3000RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	320	81	94	70	1.22	1.81	4.56	1.15	1.34
-30	(-22)	433	109	127	86	1.43	2.45	5.06	1.28	1.48
-25	(-13)	578	146	169	101	1.66	3.28	5.73	1.44	1.68
-20	(- 4)	759	191	222	116	1.91	4.32	6.53	1.64	1.91
-15	(+ 5)	978	246	287	132	2.19	5.58	7.40	1.86	2.17
-10	(+14)	1238	312	363	149	2.48	7.10	8.30	2.09	2.43

TEST CONDITIONS: @115V3000RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	279	70	82	72	1.26	1.58	3.89	0.98	1.14
-30	(-22)	389	98	114	88	1.46	2.21	4.41	1.11	1.29
-25	(-13)	531	134	156	104	1.71	3.01	5.05	1.27	1.48
-20	(- 4)	706	178	207	122	2.00	4.02	5.76	1.45	1.69
-15	(+ 5)	919	232	269	141	2.33	5.25	6.49	1.64	1.90
-10	(+14)	1172	295	343	163	2.70	6.71	7.20	1.81	2.11

TEST CONDITIONS: @115V3000RPM		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	238	60	70	73	1.32	1.34	3.24	0.82	0.95
-30	(-22)	343	87	101	90	1.52	1.95	3.82	0.96	1.12
-25	(-13)	479	121	140	108	1.79	2.72	4.45	1.12	1.30
-20	(- 4)	648	163	190	128	2.13	3.69	5.09	1.28	1.49
-15	(+ 5)	852	215	250	151	2.54	4.86	5.70	1.44	1.67
-10	(+14)	1096	276	321	177	3.00	6.28	6.23	1.57	1.83

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	472	119	138	94	1.58	2.67	4.98	1.26	1.46
-30	(-22)	622	157	182	111	1.82	3.53	5.60	1.41	1.64
-25	(-13)	816	206	239	130	2.13	4.63	6.28	1.58	1.84
-20	(- 4)	1058	267	310	151	2.48	6.02	7.04	1.77	2.06
-15	(+ 5)	1352	341	396	172	2.83	7.72	7.92	1.99	2.32
-10	(+14)	1703	429	499	191	3.16	9.76	8.94	2.25	2.62

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	400	101	117	96	1.71	2.26	4.20	1.06	1.23
-30	(-22)	550	139	161	112	1.87	3.12	4.89	1.23	1.43
-25	(-13)	744	187	218	132	2.15	4.22	5.60	1.41	1.64
-20	(- 4)	987	249	289	155	2.50	5.62	6.34	1.60	1.86
-15	(+ 5)	1283	323	376	179	2.90	7.32	7.14	1.80	2.09
-10	(+14)	1636	412	479	203	3.31	9.38	8.05	2.03	2.36

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	342	86	100	98	1.87	1.93	3.52	0.89	1.03
-30	(-22)	484	122	142	114	1.98	2.74	4.26	1.07	1.25
-25	(-13)	672	169	197	135	2.23	3.81	4.95	1.25	1.45
-20	(- 4)	908	229	266	160	2.60	5.17	5.63	1.42	1.65
-15	(+ 5)	1199	302	351	188	3.06	6.84	6.33	1.60	1.86
-10	(+14)	1548	390	454	218	3.58	8.87	7.08	1.78	2.08

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	298	75	87	98	2.05	1.69	3.00	0.75	0.88
-30	(-22)	426	107	125	115	2.11	2.41	3.73	0.94	1.09
-25	(-13)	599	151	176	138	2.36	3.40	4.37	1.10	1.28
-20	(- 4)	823	207	241	167	2.77	4.68	4.96	1.25	1.45
-15	(+ 5)	1102	278	323	201	3.31	6.29	5.51	1.39	1.62
-10	(+14)	1440	363	422	237	3.94	8.25	6.07	1.53	1.78

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 24° to Back		
3.3 PROCESS	6.35 +0.08/-0.08	[mm]	(0.250" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		