

COMPRESSOR DEFINITION

Designation	NE U6214GK
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	959UE92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	9.99	[cm ³] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.2	[kg] (24.69 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA7AC3C-115	
3 Start capacitor	243-292(250)	[µF(VAC minimum)]
4 Run capacitor	25(400)	[µF(VAC minimum)]
5 Motor protection	T1063/G9	
6 Start winding resistance	5.99	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	42.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3296	831	966	622	5.87	35.52	5.30	1.34	1.55

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2573	648	754	442	4.37	21.73	5.81	1.46	1.70
-15	(+ 5)	3072	774	900	487	4.75	26.26	6.33	1.60	1.86
-10	(+14)	3774	951	1106	531	5.12	32.65	7.11	1.79	2.08
-5	(+23)	4681	1180	1372	576	5.48	41.09	8.12	2.05	2.38
0	(+32)	5791	1459	1697	620	5.83	51.74	9.33	2.35	2.73
+5	(+41)	7106	1791	2082	664	6.18	64.77	10.69	2.69	3.13
+10	(+50)	8624	2173	2527	708	6.52	80.37	12.19	3.07	3.57

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2127	536	623	470	4.60	20.77	4.51	1.14	1.32
-15	(+ 5)	2550	643	747	524	5.05	25.19	4.87	1.23	1.43
-10	(+14)	3132	789	918	577	5.49	31.37	5.43	1.37	1.59
-5	(+23)	3874	976	1135	628	5.91	39.47	6.17	1.56	1.81
0	(+32)	4775	1203	1399	677	6.31	49.67	7.06	1.78	2.07
+5	(+41)	5835	1470	1710	724	6.70	62.14	8.07	2.03	2.36
+10	(+50)	7054	1778	2067	769	7.08	77.07	9.16	2.31	2.69

TEST CONDITIONS: @115V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1634	412	479	490	4.74	19.23	3.35	0.84	0.98
-15	(+ 5)	1995	503	585	557	5.31	23.75	3.58	0.90	1.05
-10	(+14)	2471	623	724	621	5.85	29.90	3.97	1.00	1.16
-5	(+23)	3062	772	897	681	6.37	37.87	4.49	1.13	1.31
0	(+32)	3767	949	1104	739	6.86	47.83	5.11	1.29	1.50
+5	(+41)	4588	1156	1344	793	7.32	59.95	5.80	1.46	1.70
+10	(+50)	5523	1392	1618	844	7.76	74.41	6.53	1.65	1.91

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		