

COMPRESSOR DEFINITION

Designation	NE U6214GK
Nominal Voltage/Frequency	200-230 V 50 Hz / 208-230 V 60 Hz
Engineering Number	959WB92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	200-230 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	9.99	[cm ³] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-230 V 50 Hz / 208-230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3H3C-108	
3 Start capacitor	108-130(330)	[μF(VAC minimum)]
4 Run capacitor	12.5(400)	[μF(VAC minimum)]
5 Motor protection	T1052/G9	
6 Start winding resistance	10.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.59	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	26.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3325	838	974	622	2.82	35.83	5.35	1.35	1.57

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2525	636	740	453	2.09	21.33	5.56	1.40	1.63
-15	(+ 5)	2968	748	870	492	2.26	25.38	6.05	1.53	1.77
-10	(+14)	3655	921	1071	534	2.44	31.62	6.86	1.73	2.01
-5	(+23)	4587	1156	1344	579	2.64	40.25	7.92	2.00	2.32
0	(+32)	5763	1452	1689	627	2.85	51.47	9.18	2.31	2.69
+5	(+41)	7184	1810	2105	677	3.08	65.48	10.60	2.67	3.11
+10	(+50)	8849	2230	2593	731	3.32	82.49	12.13	3.06	3.55

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2064	520	605	474	2.19	20.15	4.36	1.10	1.28
-15	(+ 5)	2451	618	718	521	2.39	24.22	4.71	1.19	1.38
-10	(+14)	3037	765	890	571	2.60	30.41	5.31	1.34	1.56
-5	(+23)	3821	963	1120	623	2.83	38.92	6.11	1.54	1.79
0	(+32)	4804	1210	1408	678	3.07	49.97	7.07	1.78	2.07
+5	(+41)	5984	1508	1754	736	3.33	63.75	8.13	2.05	2.38
+10	(+50)	7363	1856	2158	796	3.60	80.46	9.25	2.33	2.71

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1599	403	469	495	2.27	18.81	3.23	0.81	0.95
-15	(+ 5)	1910	481	560	549	2.50	22.73	3.47	0.87	1.02
-10	(+14)	2373	598	695	606	2.75	28.72	3.91	0.98	1.15
-5	(+23)	2989	753	876	665	3.01	36.98	4.50	1.13	1.32
0	(+32)	3756	947	1101	726	3.28	47.71	5.19	1.31	1.52
+5	(+41)	4676	1178	1370	790	3.57	61.11	5.94	1.50	1.74
+10	(+50)	5747	1448	1684	856	3.87	77.38	6.69	1.69	1.96

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		