

### COMPRESSOR DEFINITION

Designation	<b>NE U6214GK</b>
Nominal Voltage/Frequency	<b>200-230 V 50 Hz / 208-230 V 60 Hz</b>
Engineering Number	<b>959WB92</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	200-230 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm <sup>2</sup> ] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm <sup>2</sup> ] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	9.99	[cm <sup>3</sup> ] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-230 V 50 Hz / 208-230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-0055	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T1064	
6 Start winding resistance	10.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.59	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	26.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3289	829	964	657	3.78	35.44	5.01	1.26	1.47

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2510	633	736	466	3.12	21.17	5.38	1.36	1.58
-15	(+ 5)	3061	771	897	511	3.26	26.17	6.00	1.51	1.76
-10	(+14)	3749	945	1099	557	3.42	32.46	6.73	1.70	1.97
-5	(+23)	4575	1153	1341	604	3.59	40.18	7.57	1.91	2.22
0	(+32)	5540	1396	1623	653	3.77	49.49	8.48	2.14	2.48
+5	(+41)	6642	1674	1946	703	3.97	60.53	9.45	2.38	2.77
+10	(+50)	7882	1986	2310	755	4.18	73.45	10.45	2.63	3.06

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2045	515	599	490	3.21	20.03	4.17	1.05	1.22
-15	(+ 5)	2498	629	732	545	3.38	24.68	4.58	1.16	1.34
-10	(+14)	3072	774	900	600	3.57	30.74	5.12	1.29	1.50
-5	(+23)	3768	950	1104	656	3.77	38.35	5.75	1.45	1.68
0	(+32)	4586	1156	1344	711	3.98	47.67	6.45	1.63	1.89
+5	(+41)	5525	1392	1619	766	4.21	58.84	7.21	1.82	2.11
+10	(+50)	6585	1659	1929	822	4.44	72.01	8.01	2.02	2.35

TEST CONDITIONS: @230V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1567	395	459	510	3.27	18.42	3.07	0.77	0.90
-15	(+ 5)	1924	485	564	577	3.49	22.89	3.33	0.84	0.98
-10	(+14)	2386	601	699	643	3.72	28.88	3.71	0.93	1.09
-5	(+23)	2953	744	865	707	3.96	36.56	4.18	1.05	1.22
0	(+32)	3625	913	1062	769	4.21	46.05	4.71	1.19	1.38
+5	(+41)	4401	1109	1290	831	4.46	57.52	5.30	1.34	1.55
+10	(+50)	5282	1331	1548	892	4.73	71.11	5.92	1.49	1.73

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		