

COMPRESSOR DEFINITION

Designation	NE U6187R
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	268ME71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	9.99	[cm ³] (0.610 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.52	[kg] (23.19 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-70-31	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MST16ADK-3265	
6 Start winding resistance	6.83	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.15	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	39.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	6.90	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARIHBP Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3536	891	1036	500	5.84	27.75	7.07	1.78	2.07

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1729	436	507	282	4.61	10.81	6.13	1.55	1.80
-10	(+14)	2187	551	641	311	4.73	13.76	7.04	1.77	2.06
-5	(+23)	2752	693	806	343	4.88	17.39	8.02	2.02	2.35
0	(+32)	3421	862	1002	378	5.07	21.76	9.06	2.28	2.65
+5	(+41)	4195	1057	1229	415	5.29	26.89	10.11	2.55	2.96
+10	(+50)	5075	1279	1487	455	5.55	32.83	11.16	2.81	3.27

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1518	383	445	298	4.65	10.42	5.09	1.28	1.49
-10	(+14)	1935	488	567	332	4.82	13.36	5.82	1.47	1.71
-5	(+23)	2447	617	717	369	5.01	16.98	6.63	1.67	1.94
0	(+32)	3053	769	895	407	5.24	21.34	7.49	1.89	2.20
+5	(+41)	3752	946	1100	448	5.49	26.45	8.39	2.11	2.46
+10	(+50)	4546	1145	1332	490	5.77	32.37	9.29	2.34	2.72

TEST CONDITIONS: @115V60Hz		ARI18 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1282	323	376	310	4.65	9.79	4.15	1.04	1.21
-10	(+14)	1639	413	480	351	4.88	12.59	4.67	1.18	1.37
-5	(+23)	2079	524	609	393	5.13	16.07	5.28	1.33	1.55
0	(+32)	2602	656	762	437	5.41	20.27	5.96	1.50	1.75
+5	(+41)	3208	808	940	481	5.70	25.23	6.67	1.68	1.95
+10	(+50)	3896	982	1142	527	6.02	31.00	7.39	1.86	2.17

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		