

COMPRESSOR DEFINITION

Designation	EM T2125GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513306217

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Fan	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Fan	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3+	[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.75	[kg] (17.09 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-36/QL2-4.35 **	
3 Start capacitor	64-77(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	T0571/G6	
6 Start winding resistance	19.15	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	11.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	9.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.45	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	2.65	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1198	302	351	251	1.57	8.12	4.77	1.20	1.40

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	599	151	176	155	1.29	4.03	3.87	0.97	1.13
-35	(-31)	783	197	229	174	1.35	5.28	4.49	1.13	1.32
-30	(-22)	1001	252	293	195	1.41	6.77	5.14	1.29	1.51
-25	(-13)	1260	318	369	217	1.48	8.56	5.82	1.47	1.71
-20	(- 4)	1566	395	459	239	1.55	10.69	6.55	1.65	1.92
-15	(+ 5)	1924	485	564	262	1.62	13.22	7.33	1.85	2.15
-10	(+14)	2340	590	686	286	1.70	16.19	8.19	2.06	2.40

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	552	139	162	158	1.29	3.70	3.50	0.88	1.03
-35	(-31)	730	184	214	180	1.36	4.92	4.05	1.02	1.19
-30	(-22)	942	237	276	204	1.43	6.36	4.61	1.16	1.35
-25	(-13)	1191	300	349	230	1.51	8.08	5.19	1.31	1.52
-20	(- 4)	1485	374	435	256	1.60	10.12	5.79	1.46	1.70
-15	(+ 5)	1830	461	536	285	1.70	12.55	6.42	1.62	1.88
-10	(+14)	2230	562	653	314	1.80	15.39	7.10	1.79	2.08

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	486	122	142	156	1.29	3.25	3.12	0.79	0.91
-35	(-31)	662	167	194	182	1.37	4.44	3.63	0.92	1.06
-30	(-22)	867	219	254	210	1.45	5.85	4.13	1.04	1.21
-25	(-13)	1109	280	325	240	1.55	7.51	4.63	1.17	1.36
-20	(- 4)	1393	351	408	272	1.66	9.48	5.12	1.29	1.50
-15	(+ 5)	1725	435	505	306	1.78	11.80	5.64	1.42	1.65
-10	(+14)	2110	532	618	342	1.91	14.54	6.17	1.55	1.81

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel BP+24°to Back		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		