

COMPRESSOR DEFINITION

Designation	NT 2192GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	923EA09

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1+	[hp]
2 Displacement	22.37	[cm ³] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3N3C-122	
3 Start capacitor	130-156(250)	[µF(VAC minimum)]
4 Run capacitor	15(440)	[µF(VAC minimum)]
5 Motor protection	MST26AHK-3261	
6 Start winding resistance	8.56	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.82	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	35.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IMQ - IRAM	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3716	936	1089	742	3.45	25.19	5.01	1.26	1.47

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1729	436	507	424	2.21	11.62	4.06	1.02	1.19
-35	(-31)	2282	575	669	494	2.45	15.39	4.64	1.17	1.36
-30	(-22)	3004	757	880	565	2.72	20.32	5.33	1.34	1.56
-25	(-13)	3893	981	1141	636	3.03	26.45	6.12	1.54	1.79
-20	(- 4)	4953	1248	1451	708	3.38	33.83	6.99	1.76	2.05
-15	(+ 5)	6183	1558	1812	780	3.76	42.49	7.92	2.00	2.32
-10	(+14)	7585	1911	2223	853	4.18	52.47	8.90	2.24	2.61

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1507	380	442	424	2.20	10.11	3.55	0.90	1.04
-35	(-31)	2070	522	606	508	2.50	13.93	4.08	1.03	1.20
-30	(-22)	2779	700	814	593	2.83	18.77	4.69	1.18	1.37
-25	(-13)	3637	917	1066	677	3.18	24.66	5.36	1.35	1.57
-20	(- 4)	4645	1171	1361	763	3.56	31.66	6.09	1.53	1.78
-15	(+ 5)	5804	1462	1701	848	3.97	39.79	6.85	1.73	2.01
-10	(+14)	7113	1793	2084	933	4.40	49.11	7.62	1.92	2.23

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1285	324	377	411	2.19	8.60	3.13	0.79	0.92
-35	(-31)	1859	469	545	510	2.55	12.49	3.63	0.92	1.06
-30	(-22)	2561	645	751	610	2.93	17.26	4.19	1.06	1.23
-25	(-13)	3391	855	994	709	3.32	22.95	4.78	1.20	1.40
-20	(- 4)	4351	1096	1275	809	3.74	29.59	5.39	1.36	1.58
-15	(+ 5)	5441	1371	1594	908	4.17	37.23	6.00	1.51	1.76
-10	(+14)	6663	1679	1952	1007	4.61	45.91	6.60	1.66	1.93

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	12.7 +0.25/-0.25 [mm] (0.500" +0.010"/-0.010")
3.1.1 Material	Steel
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)
3.2 DISCHARGE	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Vertical
3.3 PROCESS	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs