

COMPRESSOR DEFINITION

Designation	EM 2X3125U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300588

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating (gauge)	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	6.09	[cm ³] (0.372 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	8.25	[kg] (18.19 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	QP2-20A	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	10(300)	[μF(VAC minimum)]
5 Motor protection	BT107-130	
6 Start winding resistance	13.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	8.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.25	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.35	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Static		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2957	745	866	279	1.29	10.12	10.60	2.67	3.11

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2996	755	878	279	1.29	10.25	10.74	2.71	3.15

TEST CONDITIONS: @220V50Hz			ASHRAEMBP46 Static		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1853	467	543	240	1.10		7.72	1.95	2.26

TEST CONDITIONS: @220V50Hz			ASHRAEMBP46 Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1883	475	552	240	1.10		7.85	1.98	2.30

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	6.1 +0.10/+0.00 [mm] (0.240" +0.004"/+0.000")
3.1.1 Material	Copper
3.1.2 Shape	Slanted 40° up + 45° to Back
3.2 DISCHARGE	4.9 +0.10/-0.05 [mm] (0.193" +0.004"/-0.002")
3.2.1 Material	Copper
3.2.2 Shape	Slanted 42° up + 24° to Back
3.3 PROCESS	6.1 +0.10/+0.00 [mm] (0.240" +0.004"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Slanted 40° up + 45° to Back
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs