

COMPRESSOR DEFINITION

Designation	NE U2168GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	959MA51

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-0055-65	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MST26ALK-3259	
6 Start winding resistance	14.26	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.25	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	22.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	4.38	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IRAM - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2539	640	744	584	3.37	17.21	4.35	1.10	1.27

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1179	297	346	321	2.50	7.93	3.66	0.92	1.07
-35	(-31)	1571	396	460	374	2.64	10.59	4.21	1.06	1.23
-30	(-22)	2065	520	605	429	2.80	13.97	4.82	1.21	1.41
-25	(-13)	2661	671	780	486	2.99	18.08	5.47	1.38	1.60
-20	(- 4)	3359	847	984	545	3.21	22.94	6.16	1.55	1.80
-15	(+ 5)	4160	1048	1219	606	3.45	28.58	6.86	1.73	2.01
-10	(+14)	5063	1276	1484	669	3.71	35.02	7.56	1.91	2.22

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1075	271	315	329	2.52	7.21	3.28	0.83	0.96
-35	(-31)	1455	367	426	388	2.68	9.80	3.76	0.95	1.10
-30	(-22)	1931	487	566	452	2.88	13.04	4.27	1.08	1.25
-25	(-13)	2503	631	733	519	3.11	16.97	4.81	1.21	1.41
-20	(- 4)	3170	799	929	591	3.39	21.60	5.35	1.35	1.57
-15	(+ 5)	3932	991	1152	667	3.69	26.96	5.90	1.49	1.73
-10	(+14)	4790	1207	1404	747	4.03	33.07	6.42	1.62	1.88

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	965	243	283	329	2.52	6.46	2.93	0.74	0.86
-35	(-31)	1330	335	390	397	2.70	8.94	3.35	0.84	0.98
-30	(-22)	1784	450	523	470	2.94	12.02	3.79	0.95	1.11
-25	(-13)	2326	586	682	550	3.23	15.74	4.23	1.07	1.24
-20	(- 4)	2957	745	867	636	3.57	20.11	4.66	1.17	1.36
-15	(+ 5)	3677	927	1077	729	3.95	25.16	5.06	1.27	1.48
-10	(+14)	4485	1130	1314	827	4.38	30.90	5.42	1.36	1.59

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		