

COMPRESSOR DEFINITION

Designation	NE K6213GK
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	959JD92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.85	[kg] (26.12 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-0016	
3 Start capacitor	64-77(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MRA6981-3265	
6 Start winding resistance	19.98	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.13	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	30.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6946	1750	2035	1104	6.63	57.18	6.29	1.59	1.84

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3300	832	967	563	4.39	20.94	5.86	1.48	1.72
-15	(+ 5)	4092	1031	1199	623	4.60	26.13	6.57	1.66	1.92
-10	(+14)	5009	1262	1468	690	4.85	32.18	7.26	1.83	2.13
-5	(+23)	6053	1525	1774	763	5.14	39.16	7.94	2.00	2.33
0	(+32)	7224	1820	2117	841	5.47	47.14	8.58	2.16	2.52
+5	(+41)	8522	2147	2497	926	5.84	56.19	9.21	2.32	2.70
+10	(+50)	9947	2507	2915	1015	6.25	66.39	9.80	2.47	2.87

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2846	717	834	595	4.49	19.94	4.78	1.20	1.40
-15	(+ 5)	3551	895	1040	664	4.74	25.03	5.35	1.35	1.57
-10	(+14)	4369	1101	1280	739	5.03	31.00	5.91	1.49	1.73
-5	(+23)	5300	1336	1553	819	5.36	37.91	6.47	1.63	1.90
0	(+32)	6345	1599	1859	903	5.73	45.83	7.02	1.77	2.06
+5	(+41)	7504	1891	2199	992	6.13	54.84	7.56	1.91	2.22
+10	(+50)	8777	2212	2572	1085	6.57	65.00	8.09	2.04	2.37

TEST CONDITIONS: @208V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2393	603	701	628	4.59	18.82	3.81	0.96	1.12
-15	(+ 5)	2994	755	877	708	4.90	23.71	4.23	1.07	1.24
-10	(+14)	3695	931	1083	792	5.24	29.47	4.66	1.18	1.37
-5	(+23)	4496	1133	1317	880	5.61	36.20	5.10	1.29	1.50
0	(+32)	5398	1360	1582	972	6.02	43.95	5.55	1.40	1.63
+5	(+41)	6401	1613	1876	1067	6.46	52.80	6.00	1.51	1.76
+10	(+50)	7505	1891	2199	1164	6.93	62.81	6.45	1.63	1.89

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		