

### COMPRESSOR DEFINITION

Designation	<b>EM C3140U</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>711WA52</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	9.04	[cm <sup>3</sup> ] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	8.2	[kg] (18.08 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021/V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	8(330)	[μF(VAC minimum)]
5 Motor protection	MRA-38172-3166	
6 Start winding resistance	13.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	9.25	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	10.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F))		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
1565	394	459	259	1.25	4.66	6.05	1.52	1.77	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	1038	261	304	181	0.89	3.07	5.72	1.44	1.68
-30	(-22)	1310	330	384	203	0.98	3.89	6.47	1.63	1.90
-25	(-13)	1644	414	482	224	1.07	4.89	7.36	1.85	2.16
-20	(- 4)	2038	514	597	244	1.16	6.08	8.36	2.11	2.45
-15	(+ 5)	2493	628	730	264	1.25	7.47	9.46	2.38	2.77
-10	(+14)	3009	758	882	283	1.34	9.05	10.65	2.68	3.12
-5	(+23)	3585	903	1051	301	1.42	10.84	11.91	3.00	3.49
0	(+32)	4223	1064	1237	319	1.50	12.84	13.22	3.33	3.87

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	972	245	285	189	0.92	2.88	5.15	1.30	1.51
-30	(-22)	1233	311	361	214	1.03	3.66	5.76	1.45	1.69
-25	(-13)	1555	392	456	239	1.14	4.62	6.49	1.64	1.90
-20	(- 4)	1938	488	568	264	1.25	5.78	7.31	1.84	2.14
-15	(+ 5)	2381	600	698	289	1.36	7.13	8.21	2.07	2.41
-10	(+14)	2884	727	845	314	1.47	8.68	9.17	2.31	2.69
-5	(+23)	3449	869	1011	339	1.59	10.43	10.17	2.56	2.98
0	(+32)	4073	1026	1194	364	1.70	12.38	11.20	2.82	3.28

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	899	227	264	197	0.96	2.66	4.57	1.15	1.34
-30	(-22)	1149	289	337	225	1.08	3.41	5.12	1.29	1.50
-25	(-13)	1458	367	427	254	1.21	4.33	5.75	1.45	1.68
-20	(- 4)	1828	461	536	284	1.34	5.45	6.45	1.63	1.89
-15	(+ 5)	2257	569	661	313	1.48	6.76	7.20	1.82	2.11
-10	(+14)	2748	692	805	344	1.62	8.27	7.99	2.01	2.34
-5	(+23)	3298	831	966	375	1.76	9.97	8.81	2.22	2.58
0	(+32)	3909	985	1145	406	1.91	11.88	9.62	2.42	2.82

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 46°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		