

### COMPRESSOR DEFINITION

Designation	<b>FMF T411U</b>
Nominal Voltage/Frequency	<b>230 V 60-150 Hz</b>
Engineering Number	<b>513805002</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	230 / 60-150	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure (Light Commercial - Curves until T.Evap -		
4.1 Evaporating temperature range	-40°C to 0°C	(-40°F to 32°F)	
5 Motor type	BPM		
6 Starting torque	LST/HST - Low/High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	11.14	[cm <sup>3</sup> ] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	430	[ml] (14.54 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.87	[kg] (23.96 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 60-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	CF10B01 N 0.1 X	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	CF10B01 N 0.1 XX A Y	
6 Start winding resistance	4.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60/150 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60/150 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60/150 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - CE - UKCA	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@115V1800RPM</b>			<b>ASHRAELBP32 Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F) 54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1191	300	349	196	1.69	3.54	6.08	1.53	1.78

TEST CONDITIONS: <b>@115V2400RPM</b>			<b>ASHRAELBP32 Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F) 54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1592	401	466	252	2.18	4.74	6.32	1.59	1.85

TEST CONDITIONS: <b>@115V3000RPM</b>			<b>ASHRAELBP32 Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F) 54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2024	510	593	322	2.68	6.02	6.28	1.58	1.84

TEST CONDITIONS: <b>@115V3600RPM</b>			<b>ASHRAELBP32 Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F) 54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2335	588	684	388	3.12	6.95	6.02	1.52	1.76

TEST CONDITIONS: <b>@115V4500RPM</b>			<b>ASHRAELBP32 Fan</b>		Evaporating temperature (Condensing temperature)		<b>-23.3°C (-9.94°F) 54.4°C (129.92°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2959	746	867	494	4.00	8.81	6.00	1.51	1.76

### E - PERFORMANCE - CURVES

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		