

### COMPRESSOR DEFINITION

Designation	<b>VEM C9C</b>
Nominal Voltage/Frequency	<b>230 V 40-150 Hz</b>
Engineering Number	<b>513906159</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	230 / 40-150	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	187 to 255 V
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	187 to 255 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	9.04	[cm <sup>3</sup> ] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	210	[ml] (7.10 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.6	[kg] (16.75 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 40-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	CF02D01 M 0.0 X/VCC32456XXXX	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	VCC3 245614F02	
6 Start winding resistance	8.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	8.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (40/150 Hz)	2.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (40/150 Hz)	2.10	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (40/150 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: <b>@220V1200RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
160	40	47	33	0.57	0.61	4.89	1.23	1.43

TEST CONDITIONS: <b>@220V1600RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
218	55	64	42	0.71	0.83	5.17	1.30	1.51

TEST CONDITIONS: <b>@220V2000RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
276	70	81	53	0.88	1.05	5.23	1.32	1.53

TEST CONDITIONS: <b>@220V3000RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
411	104	120	80	1.24	1.57	5.16	1.30	1.51

TEST CONDITIONS: <b>@220V4500RPM</b>			<b>CECOMAFLBP</b> <b>Static</b>		Evaporating temperature (Condensing temperature)		<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
553	139	162	112	0.89	2.11	4.95	1.25	1.45

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V1200RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F) )					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	119	30	35	20	0.38	0.38	5.84	1.47	1.71
-30	(-22)	163	41	48	24	0.52	0.52	6.76	1.70	1.98
-25	(-13)	215	54	63	28	0.69	0.69	7.80	1.97	2.29
-20	(- 4)	277	70	81	31	0.89	0.89	9.01	2.27	2.64
-15	(+ 5)	351	89	103	34	1.13	1.13	10.44	2.63	3.06
-10	(+14)	439	111	129	36	1.41	1.41	12.12	3.05	3.55

TEST CONDITIONS: @220V1200RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F) )					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	98	25	29	21	0.34	0.34	4.63	1.17	1.36
-30	(-22)	138	35	41	26	0.48	0.48	5.35	1.35	1.57
-25	(-13)	186	47	55	30	0.65	0.65	6.12	1.54	1.79
-20	(- 4)	244	61	71	35	0.85	0.85	6.99	1.76	2.05
-15	(+ 5)	312	79	91	39	1.09	1.09	8.00	2.02	2.34
-10	(+14)	392	99	115	43	1.37	1.37	9.20	2.32	2.70

TEST CONDITIONS: @220V1200RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F) )					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	77	19	23	21	0.29	0.29	3.59	0.90	1.05
-30	(-22)	114	29	33	27	0.43	0.43	4.26	1.07	1.25
-25	(-13)	158	40	46	32	0.60	0.60	4.91	1.24	1.44
-20	(- 4)	210	53	62	38	0.80	0.80	5.57	1.40	1.63
-15	(+ 5)	272	69	80	43	1.04	1.04	6.31	1.59	1.85
-10	(+14)	345	87	101	48	1.32	1.32	7.16	1.81	2.10

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F) )					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	165	42	48	26	0.20	0.53	6.23	1.57	1.83
-30	(-22)	223	56	65	31	0.24	0.72	7.08	1.78	2.08
-25	(-13)	293	74	86	36	0.28	0.94	8.05	2.03	2.36
-20	(- 4)	377	95	111	41	0.32	1.21	9.18	2.31	2.69
-15	(+ 5)	477	120	140	45	0.35	1.53	10.52	2.65	3.08
-10	(+14)	594	150	174	49	0.38	1.92	12.11	3.05	3.55

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	138	35	40	28	0.21	0.48	4.97	1.25	1.46
-30	(-22)	192	48	56	34	0.25	0.67	5.69	1.43	1.67
-25	(-13)	256	65	75	40	0.30	0.89	6.43	1.62	1.89
-20	(- 4)	334	84	98	46	0.35	1.16	7.26	1.83	2.13
-15	(+ 5)	426	107	125	52	0.39	1.49	8.21	2.07	2.41
-10	(+14)	533	134	156	57	0.43	1.87	9.33	2.35	2.73

TEST CONDITIONS: @220V1600RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	110	28	32	29	0.22	0.42	3.83	0.97	1.12
-30	(-22)	160	40	47	35	0.27	0.61	4.55	1.15	1.33
-25	(-13)	219	55	64	42	0.32	0.83	5.22	1.32	1.53
-20	(- 4)	289	73	85	49	0.37	1.10	5.88	1.48	1.72
-15	(+ 5)	373	94	109	57	0.43	1.43	6.59	1.66	1.93
-10	(+14)	471	119	138	64	0.49	1.81	7.37	1.86	2.16

TEST CONDITIONS: @220V2000RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	208	52	61	33	0.25	0.67	6.30	1.59	1.85
-30	(-22)	280	71	82	39	0.30	0.90	7.14	1.80	2.09
-25	(-13)	368	93	108	46	0.35	1.18	8.07	2.03	2.36
-20	(- 4)	472	119	138	52	0.40	1.52	9.15	2.30	2.68
-15	(+ 5)	596	150	175	57	0.44	1.92	10.42	2.63	3.05
-10	(+14)	742	187	218	62	0.47	2.39	11.96	3.01	3.50

TEST CONDITIONS: @220V2000RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	175	44	51	35	0.26	0.61	5.07	1.28	1.48
-30	(-22)	242	61	71	42	0.32	0.84	5.78	1.46	1.69
-25	(-13)	323	81	95	49	0.38	1.12	6.50	1.64	1.90
-20	(- 4)	419	105	123	57	0.44	1.46	7.28	1.84	2.13
-15	(+ 5)	533	134	156	65	0.49	1.86	8.18	2.06	2.40
-10	(+14)	667	168	195	72	0.55	2.34	9.26	2.33	2.71

### E - PERFORMANCE - CURVES

TEST CONDITIONS:		CECOMAF			(Condensing temperature 55°C (+131°F))					
@220V2000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%						+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	141	35	41	36	0.27	0.54	3.89	0.98	1.14	
-30 (-22)	202	51	59	44	0.33	0.77	4.63	1.17	1.36	
-25 (-13)	276	70	81	52	0.40	1.05	5.29	1.33	1.55	
-20 (- 4)	363	92	106	62	0.47	1.39	5.93	1.49	1.74	
-15 (+ 5)	467	118	137	71	0.54	1.79	6.60	1.66	1.93	
-10 (+14)	590	149	173	80	0.61	2.26	7.35	1.85	2.16	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 35°C (+95°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%						+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	307	77	90	50	0.38	0.98	6.11	1.54	1.79	
-30 (-22)	416	105	122	60	0.46	1.33	6.87	1.73	2.01	
-25 (-13)	548	138	160	71	0.54	1.76	7.73	1.95	2.27	
-20 (- 4)	706	178	207	81	0.62	2.27	8.74	2.20	2.56	
-15 (+ 5)	893	225	262	90	0.69	2.87	9.95	2.51	2.92	
-10 (+14)	1113	281	326	98	0.75	3.59	11.41	2.87	3.34	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 45°C (+113°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%						+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	256	64	75	52	0.39	0.89	4.98	1.26	1.46	
-30 (-22)	357	90	105	64	0.48	1.24	5.61	1.41	1.64	
-25 (-13)	478	120	140	76	0.58	1.66	6.26	1.58	1.84	
-20 (- 4)	623	157	183	89	0.68	2.17	6.99	1.76	2.05	
-15 (+ 5)	796	201	233	101	0.77	2.78	7.84	1.98	2.30	
-10 (+14)	998	252	293	113	0.86	3.50	8.85	2.23	2.59	

TEST CONDITIONS:		CECOMAF			(Condensing temperature 55°C (+131°F))					
@220V3000RPM		Static								
Evaporating temperature	Cooling capacity			Power consumption	Current consumption	Gas flow rate	EFFICIENCY RATE			
	+/- 5%						+/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	203	51	60	52	0.39	0.77	3.92	0.99	1.15	
-30 (-22)	296	74	87	65	0.50	1.12	4.55	1.15	1.33	
-25 (-13)	406	102	119	79	0.61	1.55	5.13	1.29	1.50	
-20 (- 4)	538	136	158	95	0.72	2.06	5.71	1.44	1.67	
-15 (+ 5)	695	175	204	110	0.84	2.66	6.34	1.60	1.86	
-10 (+14)	880	222	258	125	0.95	3.38	7.05	1.78	2.07	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	447	113	131	78	0.58	1.43	5.74	1.45	1.68
-30	(-22)	591	149	173	97	0.68	1.90	6.04	1.52	1.77
-25	(-13)	769	194	225	109	0.80	2.47	7.07	1.78	2.07
-20	(- 4)	983	248	288	116	0.91	3.16	8.49	2.14	2.49
-15	(+ 5)	1237	312	362	124	1.02	3.98	9.95	2.51	2.92
-10	(+14)	1533	386	449	138	1.12	4.95	11.11	2.80	3.25

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	387	97	113	78	0.62	1.34	4.99	1.26	1.46
-30	(-22)	518	131	152	97	0.74	1.80	5.34	1.35	1.57
-25	(-13)	681	172	199	108	0.87	2.37	6.36	1.60	1.86
-20	(- 4)	877	221	257	116	1.01	3.06	7.70	1.94	2.26
-15	(+ 5)	1111	280	326	127	1.15	3.88	9.00	2.27	2.64
-10	(+14)	1385	349	406	144	1.28	4.85	9.92	2.50	2.91

TEST CONDITIONS: @220V4500RPM		CECOMAF Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]
-35	(-31)	320	81	94	86	0.66	1.22	3.68	0.93	1.08
-30	(-22)	439	111	129	107	0.78	1.67	3.90	0.98	1.14
-25	(-13)	586	148	172	123	0.92	2.23	4.72	1.19	1.38
-20	(- 4)	766	193	224	136	1.08	2.92	5.77	1.46	1.69
-15	(+ 5)	979	247	287	153	1.25	3.75	6.73	1.69	1.97
-10	(+14)	1231	310	361	177	1.41	4.73	7.22	1.82	2.12

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 28° up + 25° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		