

COMPRESSOR DEFINITION

Designation	EM T2121U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300652

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Very Low Back Pressure		
4.1 Evaporating temperature range	-45°C to -10°C	(-49°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	5.56	[cm ³] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0015	
3 Start capacitor	43-53(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	4TM276NFBYY-53	
6 Start winding resistance		[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance		[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	7.70	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
928	234	272	178	1.27	2.76	5.20	1.31	1.52

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	573	144	168	122	0.95	1.69	4.90	1.23	1.44
-35	(-31)	535	135	157	100	0.79	1.58	4.93	1.24	1.45
-30	(-22)	858	216	251	128	0.92	2.54	6.43	1.62	1.88
-25	(-13)	1260	318	369	169	1.12	3.76	8.09	2.04	2.37
-20	(- 4)	1464	369	429	188	1.18	4.37	8.60	2.17	2.52
-15	(+ 5)	1190	300	349	146	0.90	3.56	6.69	1.68	1.96
-10	(+14)	159	40	47	8	0.06	0.48	1.03	0.26	0.30

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	506	128	148	125	0.95	1.50	4.08	1.03	1.20
-35	(-31)	414	104	121	110	0.82	1.22	3.64	0.92	1.07
-30	(-22)	706	178	207	142	0.96	2.09	4.87	1.23	1.43
-25	(-13)	1104	278	323	186	1.17	3.29	6.47	1.63	1.90
-20	(- 4)	1328	335	389	204	1.24	3.97	7.14	1.80	2.09
-15	(+ 5)	1098	277	322	160	0.95	3.29	5.58	1.41	1.64
-10	(+14)	137	34	40	18	0.10	0.41	0.50	0.13	0.15

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	483	122	142	124	0.95	1.43	3.84	0.97	1.13
-35	(-31)	320	81	94	114	0.83	0.94	2.86	0.72	0.84
-30	(-22)	567	143	166	150	0.99	1.68	3.77	0.95	1.10
-25	(-13)	944	238	277	195	1.20	2.81	5.25	1.32	1.54
-20	(- 4)	1172	295	343	212	1.26	3.50	6.02	1.52	1.76
-15	(+ 5)	971	245	285	166	0.96	2.91	4.77	1.20	1.40
-10	(+14)	64	16	19	19	0.10	0.19	0.20	0.05	0.06

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		