

### COMPRESSOR DEFINITION

Designation	EM 2YS30HLP
Nominal Voltage/Frequency	220 V 50-60 Hz
Engineering Number	513305584

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220 / 50-60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	198 to 242 V
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/10	[hp]
2 Displacement	3.00	[cm <sup>3</sup> ] (0.183 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	10.600	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.02	[kg] (15.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM189KFBYY-53	
6 Start winding resistance	9.72	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	25.77	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	3.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	0.79	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	0.88	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
307	77	90	63	0.41	1.74	4.84	1.22	1.42

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 35°C (+95°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	186	47	54		0.00	1.05	0.00	0.00	0.00
-30	(-22)	263	66	77		0.00	1.49	0.00	0.00	0.00
-25	(-13)	362	91	106		0.00	2.06	0.00	0.00	0.00
-20	(- 4)	483	122	142		0.00	2.75	0.00	0.00	0.00
-15	(+ 5)	624	157	183		0.00	3.56	0.00	0.00	0.00
-10	(+14)	784	198	230		0.00	4.49	0.00	0.00	0.00

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	148	37	43		0.00	0.84	0.00	0.00	0.00
-30	(-22)	221	56	65		0.00	1.25	0.00	0.00	0.00
-25	(-13)	318	80	93		0.00	1.80	0.00	0.00	0.00
-20	(- 4)	438	110	128		0.00	2.49	0.00	0.00	0.00
-15	(+ 5)	580	146	170		0.00	3.31	0.00	0.00	0.00
-10	(+14)	744	187	218		0.00	4.26	0.00	0.00	0.00

TEST CONDITIONS: @220V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	112	28	33		0.00	0.64	0.00	0.00	0.00
-30	(-22)	177	45	52		0.00	1.00	0.00	0.00	0.00
-25	(-13)	268	68	79		0.00	1.52	0.00	0.00	0.00
-20	(- 4)	384	97	112		0.00	2.18	0.00	0.00	0.00
-15	(+ 5)	524	132	153		0.00	2.99	0.00	0.00	0.00
-10	(+14)	687	173	201		0.00	3.93	0.00	0.00	0.00

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	80	20	23		0.00	0.45	0.00	0.00	0.00
-30	(-22)	133	34	39		0.00	0.75	0.00	0.00	0.00
-25	(-13)	214	54	63		0.00	1.22	0.00	0.00	0.00
-20	(- 4)	322	81	94		0.00	1.83	0.00	0.00	0.00
-15	(+ 5)	456	115	134		0.00	2.60	0.00	0.00	0.00
-10	(+14)	615	155	180		0.00	3.52	0.00	0.00	0.00

### F - EXTERNAL CHARACTERISTICS

1 Base plate	New Base Plate EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 30° up + 24° to Back		
3.3 PROCESS	6.35 +0.08/-0.08	[mm]	(0.250" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		