

COMPRESSOR DEFINITION

Designation	EM T6152U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513306236

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.74	[kg] (17.06 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-34/QL2-3.95 **	
3 Start capacitor	43-53(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	DRB180K52AXF	
6 Start winding resistance	21.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.95	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP_HH Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1428	360	418	205	1.31	4.81	6.98	1.76	2.05

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1104	278	324	164	1.20	3.37	6.73	1.70	1.97
-15	(+ 5)	1352	341	396	175	1.22	4.15	7.72	1.94	2.26
-10	(+14)	1624	409	476	184	1.25	5.01	8.81	2.22	2.58
-5	(+23)	1933	487	566	193	1.28	5.99	10.05	2.53	2.95
0	(+32)	2295	578	673	200	1.31	7.15	11.48	2.89	3.36
+5	(+41)	2724	686	798	207	1.33	8.55	13.13	3.31	3.85
+10	(+50)	3234	815	948	215	1.35	10.25	15.05	3.79	4.41

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	951	240	279	178	1.23	3.17	5.36	1.35	1.57
-15	(+ 5)	1181	298	346	192	1.27	3.96	6.13	1.55	1.80
-10	(+14)	1428	360	418	205	1.31	4.81	6.96	1.75	2.04
-5	(+23)	1706	430	500	216	1.35	5.78	7.87	1.98	2.31
0	(+32)	2032	512	595	228	1.40	6.93	8.92	2.25	2.61
+5	(+41)	2418	609	709	239	1.43	8.31	10.13	2.55	2.97
+10	(+50)	2879	726	844	250	1.46	9.99	11.54	2.91	3.38

TEST CONDITIONS: @220V50Hz			EN12900HH Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	827	208	242	193	1.27	3.06	4.28	1.08	1.26
-15	(+ 5)	1027	259	301	210	1.33	3.81	4.89	1.23	1.43
-10	(+14)	1238	312	363	226	1.39	4.62	5.48	1.38	1.61
-5	(+23)	1476	372	432	242	1.44	5.54	6.11	1.54	1.79
0	(+32)	1753	442	514	258	1.50	6.64	6.80	1.71	1.99
+5	(+41)	2086	526	611	274	1.54	7.97	7.61	1.92	2.23
+10	(+50)	2487	627	729	290	1.58	9.59	8.56	2.16	2.51

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel BP+24°to Back		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		