

COMPRESSOR DEFINITION

Designation	NJ 2212GS
Nominal Voltage/Frequency	380-420 V 50 Hz / 440-480 V 60 Hz
Engineering Number	947AM95

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	380-420 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	3PHASE		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/2	[hp]
2 Displacement	34.38	[cm ³] (2.098 cu.in)
2.1 Bore [mm]	42.850	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	20.4	[kg] (44.97 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	380-420 V 50 Hz / 440-480 V 60 Hz 3 ~ (Three phase)	
2 Starting device type	3PHASE	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	34HM260-50	
6 Start winding resistance		[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance		[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - UL - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @440V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5642	1422	1653	1282	2.29	38.25	4.40	1.11	1.29

E - PERFORMANCE - CURVES

TEST CONDITIONS: @440V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	2603	656	763	695	1.73	17.50	3.73	0.94	1.09
-35	(-31)	3561	897	1044	849	1.86	24.01	4.23	1.07	1.24
-30	(-22)	4831	1217	1416	1013	2.02	32.68	4.78	1.20	1.40
-25	(-13)	6411	1616	1879	1187	2.20	43.56	5.37	1.35	1.57
-20	(- 4)	8302	2092	2433	1370	2.40	56.70	6.01	1.52	1.76
-15	(+ 5)	10504	2647	3078	1562	2.62	72.18	6.70	1.69	1.96
-10	(+14)	13016	3280	3814	1764	2.86	90.03	7.44	1.87	2.18

TEST CONDITIONS: @440V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	2007	506	588	620	1.68	13.46	3.19	0.80	0.94
-35	(-31)	3045	767	892	817	1.83	20.49	3.75	0.95	1.10
-30	(-22)	4346	1095	1274	1020	2.01	29.35	4.31	1.08	1.26
-25	(-13)	5912	1490	1732	1228	2.23	40.08	4.85	1.22	1.42
-20	(- 4)	7742	1951	2268	1442	2.46	52.76	5.38	1.36	1.58
-15	(+ 5)	9835	2478	2882	1661	2.73	67.44	5.90	1.49	1.73
-10	(+14)	12191	3072	3572	1886	3.02	84.18	6.43	1.62	1.88

TEST CONDITIONS: @440V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1004	253	294	445	1.58	6.71	2.31	0.58	0.68
-35	(-31)	2173	548	637	699	1.76	14.61	3.03	0.76	0.89
-30	(-22)	3560	897	1043	955	1.97	24.00	3.68	0.93	1.08
-25	(-13)	5164	1301	1513	1212	2.22	34.94	4.26	1.07	1.25
-20	(- 4)	6985	1760	2047	1470	2.50	47.50	4.79	1.21	1.40
-15	(+ 5)	9023	2274	2644	1730	2.81	61.74	5.25	1.32	1.54
-10	(+14)	11277	2842	3304	1991	3.15	77.70	5.65	1.42	1.66

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.77 +0.08/+0.00	[mm]	(0.503" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		