

### COMPRESSOR DEFINITION

Designation	NT 6217Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	212BA06

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	20.44	[cm <sup>3</sup> ] (1.247 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2M3C-111	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	15(400)	[µF(VAC minimum)]
5 Motor protection	T0634/G9	
6 Start winding resistance	11.22	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.00	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	25.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	3.54	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ - IRAM	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
6630	1671	1943	727	3.40	42.99	9.12	2.30	2.67

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3298	831	967	430	2.15	17.84	7.66	1.93	2.25
-10	(+14)	4098	1033	1201	463	2.28	22.24	8.87	2.24	2.60
-5	(+23)	5128	1292	1502	497	2.43	27.92	10.32	2.60	3.03
0	(+32)	6387	1609	1871	533	2.58	34.94	11.98	3.02	3.51
+5	(+41)	7875	1985	2308	571	2.74	43.33	13.79	3.48	4.04
+10	(+50)	9594	2418	2811	610	2.91	53.12	15.73	3.96	4.61

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2864	722	839	461	2.26	16.72	6.21	1.57	1.82
-10	(+14)	3590	905	1052	503	2.44	21.05	7.15	1.80	2.09
-5	(+23)	4515	1138	1323	545	2.62	26.59	8.28	2.09	2.43
0	(+32)	5637	1421	1652	588	2.80	33.36	9.58	2.41	2.81
+5	(+41)	6958	1753	2039	632	2.99	41.41	11.00	2.77	3.22
+10	(+50)	8476	2136	2484	678	3.19	50.79	12.51	3.15	3.66

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2469	622	723	487	2.37	15.73	5.07	1.28	1.49
-10	(+14)	3120	786	914	541	2.60	19.95	5.76	1.45	1.69
-5	(+23)	3937	992	1154	594	2.83	25.29	6.62	1.67	1.94
0	(+32)	4921	1240	1442	648	3.06	31.79	7.60	1.91	2.23
+5	(+41)	6071	1530	1779	702	3.30	39.47	8.66	2.18	2.54
+10	(+50)	7388	1862	2165	756	3.54	48.38	9.77	2.46	2.86

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		