

COMPRESSOR DEFINITION

Designation	NT 6226GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	923BA92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1+	[hp]
2 Displacement	22.37	[cm ³] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA403C-123	
3 Start capacitor	130-156(250)	[μF(VAC minimum)]
4 Run capacitor	20(440)	[μF(VAC minimum)]
5 Motor protection	T0828/C9	
6 Start winding resistance	8.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
11450	2885	3355	1376	6.60	94.26	8.32	2.10	2.44

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	5261	1326	1541	759	3.81	33.38	6.92	1.74	2.03
-15	(+ 5)	6578	1658	1927	824	4.08	42.01	7.99	2.01	2.34
-10	(+14)	8168	2058	2393	889	4.37	52.47	9.19	2.32	2.69
-5	(+23)	10034	2529	2940	955	4.67	64.91	10.50	2.65	3.08
0	(+32)	12179	3069	3569	1022	4.97	79.48	11.91	3.00	3.49
+5	(+41)	14606	3681	4280	1091	5.28	96.32	13.39	3.37	3.92
+10	(+50)	17317	4364	5074	1160	5.59	115.58	14.93	3.76	4.38

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4488	1131	1315	814	4.05	31.43	5.52	1.39	1.62
-15	(+ 5)	5637	1421	1652	893	4.39	39.75	6.31	1.59	1.85
-10	(+14)	7017	1768	2056	972	4.74	49.80	7.22	1.82	2.11
-5	(+23)	8630	2175	2529	1051	5.10	61.74	8.21	2.07	2.41
0	(+32)	10480	2641	3071	1130	5.46	75.71	9.27	2.34	2.72
+5	(+41)	12569	3167	3683	1210	5.83	91.85	10.39	2.62	3.04
+10	(+50)	14899	3755	4366	1291	6.20	110.30	11.55	2.91	3.38

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3759	947	1101	865	4.27	29.57	4.35	1.10	1.27
-15	(+ 5)	4745	1196	1390	961	4.69	37.57	4.93	1.24	1.45
-10	(+14)	5918	1491	1734	1055	5.12	47.21	5.61	1.41	1.64
-5	(+23)	7283	1835	2134	1149	5.55	58.63	6.34	1.60	1.86
0	(+32)	8842	2228	2591	1242	5.98	71.98	7.13	1.80	2.09
+5	(+41)	10597	2670	3105	1335	6.41	87.41	7.95	2.00	2.33
+10	(+50)	12551	3163	3678	1428	6.84	105.05	8.78	2.21	2.57

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		