

COMPRESSOR DEFINITION

Designation	NT 6215Z
Nominal Voltage/Frequency	200-240 V 50 Hz / 230 V 60 Hz
Engineering Number	212AN04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	200-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-240 V 50 Hz / 230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-46	
3 Start capacitor	64-77(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0540/G8	
6 Start winding resistance	13.80	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ - IRAM - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @200V50Hz			EN12900HBP Fan		Evaporating temperature (Condensing temperature		5°C (41°F) 50°C (122°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4795	1208	1405	590	3.76		8.13	2.05	2.38

E - PERFORMANCE - CURVES

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2489	627	729	355	2.77	15.43	7.00	1.76	2.05
-10	(+14)	3175	800	930	393	2.91	19.81	8.08	2.03	2.37
-5	(+23)	3992	1006	1170	427	3.05	25.01	9.35	2.36	2.74
0	(+32)	4967	1252	1455	458	3.17	31.30	10.86	2.74	3.18
+5	(+41)	6129	1544	1796	487	3.30	38.91	12.60	3.17	3.69
+10	(+50)	7505	1891	2199	514	3.42	48.10	14.58	3.68	4.27

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2141	539	627	380	2.85	14.56	5.66	1.43	1.66
-10	(+14)	2717	685	796	425	3.03	18.57	6.38	1.61	1.87
-5	(+23)	3406	858	998	469	3.21	23.41	7.25	1.83	2.12
0	(+32)	4235	1067	1241	511	3.39	29.30	8.27	2.08	2.42
+5	(+41)	5233	1319	1533	553	3.58	36.52	9.45	2.38	2.77
+10	(+50)	6427	1620	1883	596	3.78	45.29	10.81	2.72	3.17

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	1775	447	520	405	2.95	13.43	4.37	1.10	1.28
-10	(+14)	2255	568	661	459	3.16	17.12	4.91	1.24	1.44
-5	(+23)	2829	713	829	514	3.39	21.62	5.52	1.39	1.62
0	(+32)	3526	889	1033	569	3.63	27.18	6.21	1.56	1.82
+5	(+41)	4373	1102	1281	625	3.89	34.03	6.99	1.76	2.05
+10	(+50)	5399	1361	1582	684	4.17	42.43	7.88	1.99	2.31

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		