

COMPRESSOR DEFINITION

Designation	EM 2X3113U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300761

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	L/MBP(CO Compressors) Hot Gas Defrost Not Allowed		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/7+	[hp]
2 Displacement	3.67	[cm ³] (0.224 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	10.600	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	8.2	[kg] (18.08 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	QP2-20A	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	5(350)	[μF(VAC minimum)]
5 Motor protection	DRB21K61A2	
6 Start winding resistance	13.05	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	16.47	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature	-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
512	129	150	94	0.43	1.52	5.45	1.37	1.60

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature	-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
519	131	152	96	0.44	1.54	5.41	1.36	1.59

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		