

### COMPRESSOR DEFINITION

Designation	EM X20CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	700IA98

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure (Light Commercial)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/12	[hp]
2 Displacement	3.97	[cm <sup>3</sup> ] (0.242 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.1	[kg] (15.65 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021XV230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(250)/2.5(350)/2(350)	[µF(VAC minimum)]
5 Motor protection	AE23AHNX	
6 Start winding resistance	37.74	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	68.28	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.12	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.34	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	0.41	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP-NOFAN Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
165	42	48	39	0.18	0.63	4.21	1.06	1.23

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF-NOFAN Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	119	30	35	27	0.13	0.38	4.38	1.10	1.28
-30	(-22)	167	42	49	31	0.14	0.54	5.40	1.36	1.58
-25	(-13)	224	57	66	35	0.16	0.72	6.45	1.62	1.89
-20	(- 4)	292	73	85	39	0.17	0.94	7.57	1.91	2.22
-15	(+ 5)	370	93	109	42	0.19	1.19	8.78	2.21	2.57
-10	(+14)	461	116	135	46	0.21	1.49	10.14	2.55	2.97
-5	(+23)	566	143	166	49	0.22	1.83	11.66	2.94	3.42
0	(+32)	685	173	201	51	0.23	2.22	13.38	3.37	3.92

TEST CONDITIONS: @220V50Hz		CECOMAF-NOFAN Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	107	27	31	30	0.14	0.37	3.57	0.90	1.05
-30	(-22)	149	38	44	34	0.15	0.52	4.42	1.11	1.29
-25	(-13)	199	50	58	38	0.17	0.69	5.26	1.33	1.54
-20	(- 4)	258	65	76	42	0.19	0.90	6.12	1.54	1.79
-15	(+ 5)	327	82	96	46	0.21	1.14	7.04	1.78	2.06
-10	(+14)	407	103	119	51	0.23	1.43	8.05	2.03	2.36
-5	(+23)	500	126	146	55	0.25	1.75	9.19	2.32	2.69
0	(+32)	605	152	177	58	0.27	2.13	10.48	2.64	3.07

TEST CONDITIONS: @220V50Hz		CECOMAF-NOFAN Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	84	21	25	30	0.14	0.32	2.76	0.69	0.81
-30	(-22)	122	31	36	35	0.16	0.46	3.51	0.88	1.03
-25	(-13)	166	42	49	39	0.18	0.63	4.21	1.06	1.23
-20	(- 4)	218	55	64	44	0.20	0.83	4.89	1.23	1.43
-15	(+ 5)	279	70	82	50	0.23	1.07	5.57	1.40	1.63
-10	(+14)	349	88	102	55	0.26	1.34	6.31	1.59	1.85
-5	(+23)	430	108	126	60	0.28	1.66	7.12	1.79	2.09
0	(+32)	523	132	153	65	0.31	2.02	8.05	2.03	2.36

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF-NOFAN Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	60	15	18	29	0.14	0.25	2.04	0.51	0.60
-30	(-22)	95	24	28	34	0.16	0.40	2.76	0.70	0.81
-25	(-13)	135	34	39	40	0.18	0.57	3.39	0.85	0.99
-20	(- 4)	181	46	53	46	0.21	0.76	3.94	0.99	1.16
-15	(+ 5)	234	59	69	53	0.24	0.99	4.47	1.13	1.31
-10	(+14)	296	75	87	59	0.27	1.26	4.99	1.26	1.46
-5	(+23)	367	93	108	66	0.31	1.57	5.55	1.40	1.63
0	(+32)	449	113	132	73	0.34	1.93	6.18	1.56	1.81

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 45° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		