

COMPRESSOR DEFINITION

Designation	EM C20CLT
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	701IA90

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/12	[hp]
2 Displacement	3.97	[cm ³] (0.242 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.6	[kg] (16.75 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021/V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2(350)/2.5(350)	[µF(VAC minimum)]
5 Motor protection	AE23AHNX	
6 Start winding resistance	27.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	64.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.05	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.31	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	0.40	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAE LBP-NOFAN Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
215	54	63	38	0.18	0.68	5.70	1.44	1.67

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	134	34	39	28	0.12	0.42	4.80	1.21	1.41
-30 (-22)	182	46	53	31	0.14	0.57	5.75	1.45	1.69
-25 (-13)	235	59	69	35	0.16	0.74	6.66	1.68	1.95
-20 (- 4)	297	75	87	39	0.18	0.93	7.60	1.92	2.23
-15 (+ 5)	371	93	109	43	0.19	1.17	8.67	2.18	2.54
-10 (+14)	460	116	135	46	0.21	1.45	9.95	2.51	2.92

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	111	28	32	28	0.12	0.35	4.05	1.02	1.19
-30 (-22)	160	40	47	32	0.14	0.50	5.06	1.28	1.48
-25 (-13)	214	54	63	36	0.16	0.67	5.95	1.50	1.74
-20 (- 4)	277	70	81	41	0.19	0.87	6.81	1.72	2.00
-15 (+ 5)	352	89	103	45	0.21	1.11	7.73	1.95	2.27
-10 (+14)	442	111	130	50	0.23	1.40	8.79	2.22	2.58

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	92	23	27	27	0.11	0.29	3.40	0.86	1.00
-30 (-22)	141	35	41	31	0.14	0.44	4.47	1.13	1.31
-25 (-13)	195	49	57	36	0.17	0.61	5.35	1.35	1.57
-20 (- 4)	258	65	76	42	0.19	0.81	6.13	1.55	1.80
-15 (+ 5)	333	84	98	48	0.22	1.05	6.90	1.74	2.02
-10 (+14)	423	107	124	54	0.25	1.34	7.76	1.95	2.27

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32-NOFAN Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	68	17	20	25	0.10	0.21	2.71	0.68	0.79
-30	(-22)	115	29	34	30	0.13	0.36	3.85	0.97	1.13
-25	(-13)	167	42	49	36	0.16	0.53	4.73	1.19	1.39
-20	(- 4)	229	58	67	42	0.20	0.72	5.44	1.37	1.59
-15	(+ 5)	302	76	89	50	0.23	0.95	6.07	1.53	1.78
-10	(+14)	391	99	115	58	0.26	1.23	6.72	1.69	1.97

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 45° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		