

### COMPRESSOR DEFINITION

Designation	EM C80CLT
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	701UA90

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	12.21	[cm <sup>3</sup> ] (0.745 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	23.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8.15	[kg] (17.97 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021XV230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(300)	[µF(VAC minimum)]
5 Motor protection	AE15BU	
6 Start winding resistance	23.17	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.86	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	7.27	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.25	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.52	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP-NOFAN</b> Static		Evaporating temperature (Condensing temperature	-25°C (-13°F) 55°C (131°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
552	139	162	115	0.53	2.10	4.82	1.21	1.41

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		<b>CECOMAF-NOFAN</b> Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	432	109	127	73	0.36	1.39	5.87	1.48	1.72	
-30 (-22)	565	142	165	87	0.42	1.81	6.52	1.64	1.91	
-25 (-13)	733	185	215	101	0.48	2.35	7.30	1.84	2.14	
-20 (- 4)	939	237	275	115	0.54	3.02	8.19	2.06	2.40	
-15 (+ 5)	1181	298	346	129	0.61	3.80	9.15	2.31	2.68	
-10 (+14)	1460	368	428	143	0.68	4.71	10.18	2.57	2.98	

TEST CONDITIONS: @220V50Hz		<b>CECOMAF-NOFAN</b> Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	371	93	109	79	0.37	1.29	4.73	1.19	1.39	
-30 (-22)	492	124	144	93	0.43	1.71	5.29	1.33	1.55	
-25 (-13)	646	163	189	108	0.50	2.25	5.95	1.50	1.74	
-20 (- 4)	832	210	244	124	0.57	2.90	6.69	1.69	1.96	
-15 (+ 5)	1051	265	308	140	0.65	3.67	7.48	1.88	2.19	
-10 (+14)	1303	328	382	157	0.73	4.57	8.29	2.09	2.43	

TEST CONDITIONS: @220V50Hz		<b>CECOMAF-NOFAN</b> Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
-35 (-31)	309	78	90	81	0.37	1.17	3.85	0.97	1.13	
-30 (-22)	417	105	122	96	0.44	1.59	4.33	1.09	1.27	
-25 (-13)	554	140	162	113	0.52	2.11	4.88	1.23	1.43	
-20 (- 4)	719	181	211	131	0.60	2.75	5.47	1.38	1.60	
-15 (+ 5)	914	230	268	150	0.69	3.50	6.09	1.53	1.78	
-10 (+14)	1137	286	333	170	0.79	4.36	6.70	1.69	1.96	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF-NOFAN Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	249	63	73	78	0.36	1.05	3.19	0.80	0.93
-30	(-22)	342	86	100	95	0.45	1.44	3.59	0.90	1.05
-25	(-13)	461	116	135	114	0.54	1.95	4.03	1.01	1.18
-20	(- 4)	603	152	177	135	0.63	2.56	4.48	1.13	1.31
-15	(+ 5)	770	194	226	157	0.74	3.27	4.93	1.24	1.44
-10	(+14)	962	243	282	181	0.85	4.10	5.34	1.35	1.57

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 45° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		