

### COMPRESSOR DEFINITION

Designation	EM Y5125Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	7100A72

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/8	[hp]
2 Displacement	4.53	[cm <sup>3</sup> ] (0.276 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	8.2	[kg] (18.08 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021/V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	AE37FN	
6 Start winding resistance	25.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	41.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>ASHRAEHBP46</b> Static		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
934	235	274	91	0.53	3.29	10.26	2.59	3.01

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		<b>ASHRAE46</b> Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	467	118	137	53	0.40	1.40	8.88	2.24	2.60
-10	(+14)	586	148	172	57	0.41	1.76	10.19	2.57	2.99
-5	(+23)	730	184	214	62	0.43	2.19	11.88	2.99	3.48
0	(+32)	900	227	264	65	0.44	2.71	13.94	3.51	4.08
+5	(+41)	1096	276	321	67	0.45	3.31	16.35	4.12	4.79
+10	(+50)	1317	332	386	69	0.45	3.99	19.13	4.82	5.61

TEST CONDITIONS: @220V50Hz		<b>ASHRAE46</b> Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	408	103	120	56	0.41	1.31	7.32	1.84	2.15
-10	(+14)	514	129	150	62	0.43	1.66	8.26	2.08	2.42
-5	(+23)	643	162	188	68	0.45	2.08	9.44	2.38	2.77
0	(+32)	797	201	234	73	0.46	2.58	10.86	2.74	3.18
+5	(+41)	976	246	286	78	0.48	3.17	12.52	3.16	3.67
+10	(+50)	1179	297	345	82	0.49	3.85	14.42	3.63	4.22

TEST CONDITIONS: @220V50Hz		<b>ASHRAE46</b> Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	344	87	101	59	0.42	1.20	5.80	1.46	1.70
-10	(+14)	437	110	128	66	0.44	1.53	6.60	1.66	1.94
-5	(+23)	553	139	162	74	0.46	1.94	7.53	1.90	2.21
0	(+32)	692	174	203	81	0.49	2.43	8.57	2.16	2.51
+5	(+41)	854	215	250	88	0.51	3.02	9.72	2.45	2.85
+10	(+50)	1040	262	305	95	0.54	3.69	10.98	2.77	3.22

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 45° to Back		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		