

### COMPRESSOR DEFINITION

Designation	FMS A9C
Nominal Voltage/Frequency	230 V 90-315 Hz
Engineering Number	518000018

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	230 / 90-315	[ V / Hz ]	
4 Application type	Low-Medium Back Pressure (Hot Gas Defrost not allowed)		
4.1 Evaporating temperature range	-35°C to 0°C	(-31°F to 32°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/7	[hp]
2 Displacement	6.51	[cm <sup>3</sup> ] (0.397 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	18.800	
3 Lubricant charge	140	[ml] (4.73 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	3.58	[kg] (7.89 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 90-315 Hz 3~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	CF02F01L	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	CF02F01 L 00 XX F	
6 Start winding resistance	17.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	17.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (90/315 Hz)	2.17	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (90/315 Hz)	1.25	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (90/315 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	TUV - UL - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V1800RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
235	59	69	39	0.75	0.74	6.06	1.53	1.78	

TEST CONDITIONS: @115V2800RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
351	88	103	57	1.12	1.10	6.14	1.55	1.80	

TEST CONDITIONS: @115V4000RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
515	130	151	85	1.51	1.62	6.08	1.53	1.78	

TEST CONDITIONS: @115V6300RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
734	185	215	133	2.31	2.30	5.53	1.39	1.62	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V1800RPM		ASHRAE32 Static				(Condensing temperature 35°C (+95°F) )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
°C (°F)										
-35 (-31)	127	32	37	23	0.48	0.40	5.41	1.36	1.59	
-30 (-22)	177	45	52	27	0.55	0.56	6.48	1.63	1.90	
-25 (-13)	238	60	70	31	0.63	0.75	7.55	1.90	2.21	
-20 (- 4)	310	78	91	36	0.71	0.97	8.70	2.19	2.55	
-15 (+ 5)	396	100	116	40	0.79	1.25	9.98	2.52	2.93	
-10 (+14)	497	125	146	43	0.86	1.57	11.47	2.89	3.36	
-5 (+23)	614	155	180	46	0.91	1.94	13.22	3.33	3.87	
0 (+32)	749	189	220	48	0.94	2.37	15.30	3.86	4.48	

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V1800RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	119	30	35	25	0.50	0.37	4.82	1.21	1.41
-30	(-22)	167	42	49	29	0.58	0.52	5.74	1.45	1.68
-25	(-13)	225	57	66	34	0.68	0.71	6.61	1.66	1.94
-20	(- 4)	296	74	87	39	0.78	0.93	7.48	1.88	2.19
-15	(+ 5)	379	95	111	45	0.88	1.19	8.42	2.12	2.47
-10	(+14)	477	120	140	50	0.98	1.51	9.50	2.39	2.78
-5	(+23)	592	149	173	55	1.06	1.87	10.78	2.72	3.16
0	(+32)	724	183	212	59	1.13	2.30	12.33	3.11	3.61

TEST CONDITIONS: @115V1800RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	103	26	30	25	0.50	0.32	4.16	1.05	1.22
-30	(-22)	151	38	44	30	0.60	0.47	5.06	1.28	1.48
-25	(-13)	210	53	61	36	0.72	0.66	5.84	1.47	1.71
-20	(- 4)	280	71	82	43	0.84	0.88	6.55	1.65	1.92
-15	(+ 5)	363	91	106	50	0.97	1.14	7.28	1.83	2.13
-10	(+14)	461	116	135	57	1.09	1.45	8.08	2.04	2.37
-5	(+23)	575	145	169	64	1.21	1.82	9.01	2.27	2.64
0	(+32)	707	178	207	70	1.31	2.24	10.15	2.56	2.98

TEST CONDITIONS: @115V2800RPM		ASHRAE32 Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	204	51	60	36	0.72	0.64	5.68	1.43	1.67
-30	(-22)	277	70	81	42	0.83	0.87	6.58	1.66	1.93
-25	(-13)	368	93	108	49	0.95	1.15	7.56	1.90	2.21
-20	(- 4)	479	121	140	55	1.07	1.50	8.64	2.18	2.53
-15	(+ 5)	611	154	179	62	1.19	1.92	9.86	2.48	2.89
-10	(+14)	766	193	225	68	1.29	2.42	11.25	2.83	3.30
-5	(+23)	947	239	278	74	1.38	2.99	12.84	3.24	3.76
0	(+32)	1154	291	338	78	1.45	3.66	14.67	3.70	4.30

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V2800RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	191	48	56	37	0.74	0.60	5.13	1.29	1.50
-30	(-22)	260	65	76	44	0.87	0.81	5.88	1.48	1.72
-25	(-13)	347	87	102	52	1.01	1.09	6.66	1.68	1.95
-20	(- 4)	454	114	133	60	1.16	1.43	7.50	1.89	2.20
-15	(+ 5)	582	147	171	69	1.30	1.83	8.44	2.13	2.47
-10	(+14)	734	185	215	77	1.44	2.32	9.51	2.40	2.79
-5	(+23)	911	230	267	85	1.57	2.88	10.74	2.71	3.15
0	(+32)	1115	281	327	92	1.68	3.53	12.16	3.06	3.56

TEST CONDITIONS: @115V2800RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	167	42	49	37	0.73	0.52	4.57	1.15	1.34
-30	(-22)	234	59	69	45	0.88	0.73	5.27	1.33	1.54
-25	(-13)	320	81	94	54	1.04	1.00	5.96	1.50	1.75
-20	(- 4)	426	107	125	64	1.21	1.34	6.68	1.68	1.96
-15	(+ 5)	553	139	162	74	1.39	1.74	7.44	1.88	2.18
-10	(+14)	703	177	206	85	1.56	2.22	8.29	2.09	2.43
-5	(+23)	879	222	258	95	1.73	2.78	9.26	2.33	2.71
0	(+32)	1082	273	317	105	1.88	3.43	10.37	2.61	3.04

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	288	73	84	53	1.02	0.90	5.42	1.37	1.59
-30	(-22)	403	101	118	63	1.20	1.26	6.35	1.60	1.86
-25	(-13)	530	134	155	73	1.38	1.66	7.25	1.83	2.13
-20	(- 4)	678	171	199	83	1.54	2.13	8.20	2.07	2.40
-15	(+ 5)	854	215	250	92	1.70	2.69	9.24	2.33	2.71
-10	(+14)	1066	269	312	102	1.86	3.36	10.41	2.62	3.05
-5	(+23)	1321	333	387	112	2.02	4.18	11.78	2.97	3.45
0	(+32)	1627	410	477	123	2.18	5.16	13.39	3.37	3.92

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	252	63	74	52	1.01	0.79	4.83	1.22	1.42
-30	(-22)	369	93	108	65	1.23	1.16	5.66	1.43	1.66
-25	(-13)	497	125	146	77	1.44	1.56	6.43	1.62	1.88
-20	(- 4)	645	162	189	89	1.65	2.03	7.22	1.82	2.11
-15	(+ 5)	819	206	240	102	1.85	2.58	8.06	2.03	2.36
-10	(+14)	1028	259	301	114	2.04	3.24	9.02	2.27	2.64
-5	(+23)	1279	322	375	126	2.24	4.04	10.13	2.55	2.97
0	(+32)	1579	398	463	139	2.44	5.01	11.46	2.89	3.36

TEST CONDITIONS: @115V4000RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	213	54	62	49	0.96	0.67	4.33	1.09	1.27
-30	(-22)	333	84	98	65	1.23	1.05	5.11	1.29	1.50
-25	(-13)	464	117	136	80	1.48	1.46	5.82	1.47	1.71
-20	(- 4)	612	154	179	94	1.72	1.92	6.51	1.64	1.91
-15	(+ 5)	786	198	230	109	1.96	2.47	7.22	1.82	2.12
-10	(+14)	993	250	291	124	2.20	3.13	8.02	2.02	2.35
-5	(+23)	1240	313	363	138	2.43	3.92	8.95	2.26	2.62
0	(+32)	1536	387	450	154	2.67	4.87	10.07	2.54	2.95

TEST CONDITIONS: @115V6300RPM		ASHRAE32 Static			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	414	104	121	86	1.61	1.30	4.85	1.22	1.42
-30	(-22)	566	143	166	100	1.87	1.77	5.63	1.42	1.65
-25	(-13)	753	190	221	118	2.16	2.36	6.39	1.61	1.87
-20	(- 4)	976	246	286	136	2.46	3.07	7.15	1.80	2.09
-15	(+ 5)	1237	312	362	155	2.75	3.89	7.96	2.01	2.33
-10	(+14)	1537	387	451	174	3.01	4.85	8.85	2.23	2.59
-5	(+23)	1879	474	551	190	3.23	5.94	9.88	2.49	2.90
0	(+32)	2263	570	663	204	3.38	7.17	11.08	2.79	3.25

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V6300RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	380	96	111	86	1.61	1.19	4.41	1.11	1.29
-30	(-22)	529	133	155	103	1.91	1.66	5.11	1.29	1.50
-25	(-13)	708	178	207	123	2.23	2.22	5.79	1.46	1.70
-20	(- 4)	919	232	269	142	2.55	2.89	6.47	1.63	1.90
-15	(+ 5)	1164	293	341	161	2.84	3.66	7.22	1.82	2.12
-10	(+14)	1444	364	423	179	3.09	4.56	8.06	2.03	2.36
-5	(+23)	1761	444	516	195	3.28	5.57	9.04	2.28	2.65
0	(+32)	2116	533	620	207	3.39	6.71	10.20	2.57	2.99

TEST CONDITIONS: @115V6300RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	346	87	101	84	1.60	1.08	4.11	1.03	1.20
-30	(-22)	499	126	146	106	1.96	1.57	4.70	1.18	1.38
-25	(-13)	679	171	199	129	2.33	2.13	5.28	1.33	1.55
-20	(- 4)	886	223	260	151	2.68	2.79	5.88	1.48	1.72
-15	(+ 5)	1123	283	329	172	2.99	3.54	6.54	1.65	1.92
-10	(+14)	1391	350	408	190	3.25	4.39	7.31	1.84	2.14
-5	(+23)	1691	426	496	206	3.43	5.35	8.23	2.07	2.41
0	(+32)	2026	510	594	217	3.52	6.42	9.33	2.35	2.73

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal ES/FMS		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted parallel to Base Plate		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 74° up + 0° back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		