

COMPRESSOR DEFINITION

Designation	NE U6212Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	268GA92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.13	[kg] (24.54 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRP-0012	
3 Start capacitor	53-64(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0964/G6	
6 Start winding resistance	27.92	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.53	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	20.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	3.90	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900HBP Fan		Evaporating temperature (Condensing temperature		5°C (41°F) 50°C (122°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4335	1092	1270	573	3.64	31.89	7.56	1.91	2.22

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	2196	553	643	350	3.10	13.63	6.27	1.58	1.84
-10	(+14)	2774	699	813	383	3.15	17.29	7.25	1.83	2.12
-5	(+23)	3476	876	1019	419	3.23	21.77	8.29	2.09	2.43
0	(+32)	4305	1085	1261	458	3.33	27.13	9.40	2.37	2.75
+5	(+41)	5258	1325	1541	499	3.47	33.39	10.53	2.65	3.09
+10	(+50)	6337	1597	1857	543	3.64	40.61	11.68	2.94	3.42

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1880	474	551	373	3.14	12.78	5.04	1.27	1.48
-10	(+14)	2412	608	707	413	3.21	16.49	5.84	1.47	1.71
-5	(+23)	3052	769	894	455	3.30	20.98	6.71	1.69	1.97
0	(+32)	3800	958	1114	500	3.43	26.30	7.61	1.92	2.23
+5	(+41)	4657	1174	1365	546	3.58	32.50	8.53	2.15	2.50
+10	(+50)	5623	1417	1648	595	3.76	39.62	9.44	2.38	2.77

TEST CONDITIONS: @220V50Hz		EN12900 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+ 5)	1536	387	450	394	3.18	11.61	3.91	0.98	1.14
-10	(+14)	2028	511	594	441	3.28	15.41	4.59	1.16	1.34
-5	(+23)	2610	658	765	491	3.39	19.96	5.31	1.34	1.56
0	(+32)	3284	828	962	543	3.53	25.31	6.05	1.52	1.77
+5	(+41)	4050	1020	1187	597	3.70	31.50	6.79	1.71	1.99
+10	(+50)	4906	1236	1438	654	3.90	38.56	7.51	1.89	2.20

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		