

COMPRESSOR DEFINITION

Designation	NE U6220GK
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	959TD92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.5	[kg] (25.35 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AH3C-648	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	15(400)	[µF(VAC minimum)]
5 Motor protection	T0558/G9	
6 Start winding resistance	10.53	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.92	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	34.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4630	1167	1357	961	4.67	49.89	4.82	1.21	1.41

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3520	887	1032	690	3.69	29.64	5.09	1.28	1.49
-15	(+ 5)	4218	1063	1236	759	3.92	36.14	5.56	1.40	1.63
-10	(+14)	5136	1294	1505	833	4.19	44.51	6.17	1.56	1.81
-5	(+23)	6309	1590	1849	912	4.49	55.38	6.92	1.74	2.03
0	(+32)	7773	1959	2278	995	4.82	69.37	7.81	1.97	2.29
+5	(+41)	9563	2410	2802	1081	5.18	87.11	8.84	2.23	2.59
+10	(+50)	11712	2952	3432	1171	5.57	109.20	10.01	2.52	2.93

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2917	735	855	727	3.80	28.53	4.01	1.01	1.17
-15	(+ 5)	3525	888	1033	805	4.08	34.85	4.38	1.10	1.28
-10	(+14)	4310	1086	1263	884	4.38	43.13	4.87	1.23	1.43
-5	(+23)	5306	1337	1555	966	4.70	54.00	5.49	1.38	1.61
0	(+32)	6549	1650	1919	1050	5.04	68.08	6.24	1.57	1.83
+5	(+41)	8073	2034	2365	1136	5.40	86.00	7.11	1.79	2.08
+10	(+50)	9913	2498	2905	1222	5.78	108.37	8.11	2.04	2.38

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2291	577	671	755	3.89	27.00	3.05	0.77	0.89
-15	(+ 5)	2781	701	815	844	4.22	33.03	3.29	0.83	0.96
-10	(+14)	3403	858	997	933	4.56	41.12	3.64	0.92	1.07
-5	(+23)	4194	1057	1229	1023	4.92	51.89	4.10	1.03	1.20
0	(+32)	5186	1307	1520	1112	5.29	65.96	4.67	1.18	1.37
+5	(+41)	6416	1617	1880	1200	5.67	83.97	5.35	1.35	1.57
+10	(+50)	7919	1996	2320	1288	6.06	106.52	6.15	1.55	1.80

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		