

### COMPRESSOR DEFINITION

Designation	NJ 7231F
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	144EA11

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-22		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Air Conditioning		
4.1 Evaporating temperature range	0°C to 15°C	(32°F to 59°F)	
5 Motor type	PSC		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	21.7	[kgf/cm <sup>2</sup> ] (309 psig)	/ °C - °F
9.2 Peak	24.2	[kgf/cm <sup>2</sup> ] (344 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	26.11	[cm <sup>3</sup> ] (1.593 cu.in)
2.1 Bore [mm]	41.770	
2.2 Stroke [mm]	19.066	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO46	
4 Weight (with oil charge)	20.3	[kg] (44.75 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PSC	
2.1 Starting device		
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	25(440)	[µF(VAC minimum)]
5 Motor protection	CST00AKN - 3031	
6 Start winding resistance	7.76	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.78	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
12303	3100	3605	1460	6.77	75.98	8.43	2.12	2.47

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F) )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	12992	3274	3807	1096	5.36	68.72	11.85	2.99	3.47
+5 (+41)	15529	3913	4550	1125	5.58	84.64	13.80	3.48	4.05
+10 (+50)	18491	4660	5418	1146	5.71	98.68	16.14	4.07	4.73
+15 (+59)	21877	5513	6411	1159	5.76	0.37	18.87	4.76	5.53

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F) )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	11196	2821	3281	1210	5.82	63.87	9.26	2.33	2.71
+5 (+41)	13478	3397	3949	1272	6.10	77.26	10.59	2.67	3.10
+10 (+50)	16093	4056	4716	1318	6.30	92.85	12.20	3.08	3.58
+15 (+59)	19041	4798	5579	1350	6.42	0.16	14.11	3.56	4.13

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F) )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
0 (+32)	9326	2350	2733	1330	6.30	57.62	7.01	1.77	2.05
+5 (+41)	11340	2858	3323	1425	6.64	68.79	7.96	2.01	2.33
+10 (+50)	13594	3426	3983	1498	6.91	86.24	9.08	2.29	2.66
+15 (+59)	16088	4054	4714	1549	7.11	- 0.53	10.38	2.62	3.04

### F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8 +0.07/+0.00	[mm]	(0.315" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		