

COMPRESSOR DEFINITION

Designation	NE K6213GK
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	959BG92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2+	[hp]
2 Displacement	12.11	[cm ³] (0.739 cu.in)
2.1 Bore [mm]	27.775	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2AE3C-105	
3 Start capacitor	189-227(165)	[μF(VAC minimum)]
4 Run capacitor	30(440)	[μF(VAC minimum)]
5 Motor protection	T0826/G9	
6 Start winding resistance	5.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.67	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	51.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	10.93	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
7050	1777	2066	1055	10.55	58.04	6.68	1.68	1.96

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3259	821	955	575	7.01	20.67	5.66	1.43	1.66
-15	(+ 5)	4053	1021	1188	628	7.36	25.89	6.46	1.63	1.89
-10	(+14)	4985	1256	1461	686	7.75	32.03	7.27	1.83	2.13
-5	(+23)	6056	1526	1774	748	8.19	39.18	8.10	2.04	2.37
0	(+32)	7263	1830	2128	815	8.67	47.40	8.91	2.25	2.61
+5	(+41)	8609	2170	2523	887	9.21	56.77	9.71	2.45	2.85
+10	(+50)	10093	2543	2957	964	9.79	67.36	10.47	2.64	3.07

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2816	710	825	603	7.13	19.74	4.67	1.18	1.37
-15	(+ 5)	3509	884	1028	665	7.57	24.74	5.28	1.33	1.55
-10	(+14)	4334	1092	1270	730	8.05	30.75	5.94	1.50	1.74
-5	(+23)	5289	1333	1550	799	8.56	37.82	6.62	1.67	1.94
0	(+32)	6376	1607	1868	871	9.11	46.05	7.32	1.84	2.14
+5	(+41)	7594	1914	2225	947	9.70	55.50	8.02	2.02	2.35
+10	(+50)	8943	2254	2620	1026	10.32	66.23	8.71	2.19	2.55

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2448	617	717	635	7.31	19.24	3.85	0.97	1.13
-15	(+ 5)	3017	760	884	708	7.86	23.89	4.26	1.07	1.25
-10	(+14)	3711	935	1088	782	8.42	29.61	4.74	1.19	1.39
-5	(+23)	4530	1142	1327	859	9.01	36.48	5.27	1.33	1.54
0	(+32)	5474	1379	1604	937	9.62	44.57	5.84	1.47	1.71
+5	(+41)	6541	1648	1917	1018	10.26	53.96	6.43	1.62	1.88
+10	(+50)	7734	1949	2266	1100	10.93	64.70	7.03	1.77	2.06

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.03 +0.07/+0.00	[mm]	(0.316" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		