

### COMPRESSOR DEFINITION

Designation	NE U6217U
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	863JE92

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm <sup>3</sup> ] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVAH7AA3C-571	
3 Start capacitor	243-292(250)	[µF(VAC minimum)]
4 Run capacitor	30(400)	[µF(VAC minimum)]
5 Motor protection	T0736/G9	
6 Start winding resistance	3.81	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.96	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	45.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	9.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
7958	2005	2332	923	8.52	27.24	8.62	2.17	2.53

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3749	945	1098	491	4.75	10.58	7.62	1.92	2.23
-15	(+ 5)	4582	1155	1343	533	5.10	12.98	8.60	2.17	2.52
-10	(+14)	5562	1402	1630	577	5.47	15.82	9.64	2.43	2.82
-5	(+23)	6687	1685	1960	623	5.87	19.11	10.74	2.71	3.15
0	(+32)	7959	2006	2332	670	6.28	22.87	11.87	2.99	3.48
+5	(+41)	9376	2363	2747	719	6.71	27.12	13.03	3.28	3.82
+10	(+50)	10939	2757	3205	770	7.17	31.88	14.21	3.58	4.16

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3259	821	955	526	5.01	9.94	6.19	1.56	1.82
-15	(+ 5)	4020	1013	1178	580	5.47	12.31	6.93	1.75	2.03
-10	(+14)	4913	1238	1440	635	5.95	15.12	7.74	1.95	2.27
-5	(+23)	5939	1497	1740	690	6.43	18.36	8.61	2.17	2.52
0	(+32)	7097	1789	2080	746	6.94	22.08	9.52	2.40	2.79
+5	(+41)	8389	2114	2458	803	7.45	26.28	10.45	2.63	3.06
+10	(+50)	9812	2473	2875	860	7.98	30.99	11.41	2.87	3.34

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2810	708	824	554	5.27	9.36	5.08	1.28	1.49
-15	(+ 5)	3492	880	1023	624	5.85	11.68	5.60	1.41	1.64
-10	(+14)	4292	1082	1258	692	6.44	14.43	6.19	1.56	1.82
-5	(+23)	5213	1314	1527	760	7.03	17.62	6.85	1.73	2.01
0	(+32)	6252	1576	1832	827	7.64	21.28	7.56	1.90	2.21
+5	(+41)	7412	1868	2172	894	8.25	25.42	8.30	2.09	2.43
+10	(+50)	8690	2190	2546	960	8.87	30.07	9.05	2.28	2.65

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		