

### COMPRESSOR DEFINITION

Designation	NE U6217U
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	863JE92

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.28	[cm <sup>3</sup> ] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.6	[kg] (25.57 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-65-31	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0873/C9	
6 Start winding resistance	3.81	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.96	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	45.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	9.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
7726	1947	2264	1012	10.34	26.44	7.63	1.92	2.24

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3695	931	1083	521	6.28	10.43	7.09	1.79	2.08
-15	(+ 5)	4506	1135	1320	567	6.62	12.77	7.96	2.01	2.33
-10	(+14)	5465	1377	1601	614	6.97	15.55	8.90	2.24	2.61
-5	(+23)	6572	1656	1926	664	7.35	18.78	9.89	2.49	2.90
0	(+32)	7827	1972	2293	716	7.75	22.50	10.92	2.75	3.20
+5	(+41)	9230	2326	2705	770	8.17	26.70	11.98	3.02	3.51
+10	(+50)	10781	2717	3159	826	8.61	31.42	13.05	3.29	3.83

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3249	819	952	561	6.53	9.91	5.79	1.46	1.70
-15	(+ 5)	3992	1006	1170	620	6.98	12.23	6.44	1.62	1.89
-10	(+14)	4864	1226	1425	681	7.45	14.97	7.14	1.80	2.09
-5	(+23)	5866	1478	1719	742	7.94	18.14	7.90	1.99	2.32
0	(+32)	6997	1763	2050	805	8.44	21.77	8.70	2.19	2.55
+5	(+41)	8256	2081	2419	868	8.96	25.87	9.52	2.40	2.79
+10	(+50)	9645	2430	2826	932	9.50	30.46	10.35	2.61	3.03

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2762	696	809	594	6.79	9.21	4.66	1.17	1.37
-15	(+ 5)	3443	868	1009	669	7.32	11.52	5.14	1.30	1.51
-10	(+14)	4234	1067	1241	744	7.87	14.23	5.69	1.43	1.67
-5	(+23)	5136	1294	1505	818	8.42	17.36	6.27	1.58	1.84
0	(+32)	6148	1549	1802	892	8.99	20.93	6.90	1.74	2.02
+5	(+41)	7271	1832	2130	966	9.58	24.94	7.54	1.90	2.21
+10	(+50)	8503	2143	2492	1039	10.17	29.42	8.18	2.06	2.40

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		