

### COMPRESSOR DEFINITION

Designation	NJ X2215U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	887FA21

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure R290		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm <sup>2</sup> ] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1 3/4	[hp]
2 Displacement	37.88	[cm <sup>3</sup> ] (2.312 cu.in)
2.1 Bore [mm]	44.980	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	22	[kg] (48.50 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3H3C-108	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	20(400)	[µF(VAC minimum)]
5 Motor protection	15HM1994-248	
6 Start winding resistance	4.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.78	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	34.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900LBP Fan		Evaporating temperature (Condensing temperature		-35°C (-31°F) 40°C (104°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3192	804	935	760	4.08	10.69	4.20	1.06	1.23

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	2640	665	773	634	3.50	8.43	4.15	1.05	1.22
-35	(-31)	3494	881	1024	737	3.93	11.20	4.75	1.20	1.39
-30	(-22)	4554	1147	1334	842	4.38	14.64	5.42	1.37	1.59
-25	(-13)	5817	1466	1705	946	4.83	18.77	6.15	1.55	1.80
-20	(- 4)	7285	1836	2135	1051	5.30	23.62	6.93	1.75	2.03
-15	(+ 5)	8957	2257	2625	1156	5.77	29.19	7.75	1.95	2.27
-10	(+14)	10833	2730	3174	1261	6.26	35.52	8.58	2.16	2.52

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	2206	556	646	662	3.58	7.72	3.33	0.84	0.98
-35	(-31)	2957	745	866	774	4.06	10.39	3.82	0.96	1.12
-30	(-22)	3882	978	1138	890	4.57	13.68	4.36	1.10	1.28
-25	(-13)	4981	1255	1460	1008	5.10	17.62	4.93	1.24	1.45
-20	(- 4)	6254	1576	1833	1131	5.65	22.23	5.53	1.39	1.62
-15	(+ 5)	7701	1941	2257	1257	6.23	27.53	6.13	1.55	1.80
-10	(+14)	9322	2349	2732	1386	6.83	33.54	6.73	1.70	1.97

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1701	429	498	663	3.59	6.62	2.57	0.65	0.75
-35	(-31)	2361	595	692	790	4.14	9.21	2.98	0.75	0.87
-30	(-22)	3166	798	928	925	4.73	12.39	3.42	0.86	1.00
-25	(-13)	4114	1037	1205	1065	5.35	16.17	3.86	0.97	1.13
-20	(- 4)	5206	1312	1525	1212	6.02	20.58	4.30	1.08	1.26
-15	(+ 5)	6441	1623	1887	1366	6.72	25.64	4.72	1.19	1.38
-10	(+14)	7821	1971	2292	1526	7.46	31.37	5.12	1.29	1.50

### F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.81 +0.04/-0.04	[mm]	(0.504" +0.002"/-0.002")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	8.04 +0.04/-0.04	[mm]	(0.317" +0.002"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted J		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		