

COMPRESSOR DEFINITION

Designation	EM 2S60CLP
Nominal Voltage/Frequency	220 V 60 Hz
Engineering Number	513304610

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	198 to 242 V
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/6	[hp]
2 Displacement	9.04	[cm ³] (0.552 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.06	[kg] (15.56 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	QPS2-A22MG1/QPS2-A22MG1 092	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	5TM283KFBYY-53	
6 Start winding resistance	19.92	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	17.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	5.72	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.43	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	1.56	[A] - Measured according to UL 984
11 Approval boards certification	CE - TUV - UKCA	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
597	150	175	119	0.78	1.87	5.01	1.26	1.47

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	352	89	103	81	0.67	1.10	4.35	1.10	1.27
-30 (-22)	476	120	140	92	0.70	1.49	5.15	1.30	1.51
-25 (-13)	634	160	186	106	0.74	1.99	6.00	1.51	1.76
-20 (- 4)	825	208	242	120	0.79	2.59	6.88	1.73	2.02
-15 (+ 5)	1046	263	306	135	0.84	3.29	7.78	1.96	2.28
-10 (+14)	1295	326	380	150	0.89	4.09	8.67	2.19	2.54

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	320	81	94	82	0.67	1.00	3.92	0.99	1.15
-30 (-22)	438	110	128	95	0.70	1.37	4.62	1.16	1.35
-25 (-13)	591	149	173	110	0.75	1.85	5.36	1.35	1.57
-20 (- 4)	779	196	228	126	0.81	2.45	6.13	1.55	1.80
-15 (+ 5)	998	252	293	144	0.87	3.14	6.92	1.74	2.03
-10 (+14)	1249	315	366	163	0.94	3.94	7.69	1.94	2.25

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	291	73	85	82	0.67	0.91	3.55	0.90	1.04
-30 (-22)	399	101	117	96	0.71	1.25	4.17	1.05	1.22
-25 (-13)	545	137	160	113	0.76	1.71	4.82	1.21	1.41
-20 (- 4)	726	183	213	132	0.83	2.28	5.49	1.38	1.61
-15 (+ 5)	941	237	276	152	0.91	2.96	6.17	1.55	1.81
-10 (+14)	1189	300	348	174	0.99	3.75	6.84	1.72	2.00

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	267	67	78	82	0.67	0.84	3.23	0.81	0.95
-30	(-22)	362	91	106	97	0.71	1.13	3.76	0.95	1.10
-25	(-13)	496	125	145	115	0.77	1.56	4.33	1.09	1.27
-20	(- 4)	668	168	196	136	0.84	2.10	4.91	1.24	1.44
-15	(+ 5)	875	220	256	159	0.93	2.76	5.50	1.39	1.61
-10	(+14)	1116	281	327	184	1.03	3.52	6.07	1.53	1.78

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EG/F/AMEM Version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel BP+24°to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted parallel BP+45°to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		