

COMPRESSOR DEFINITION

Designation	EM 2U60HLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513305521

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.54	[cm ³] (0.338 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	7.4	[kg] (16.31 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MD3/8EA17B3/8EA17C3/8EA17E61/8EA17E62/8EA17E63	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(300)	[µF(VAC minimum)]
5 Motor protection	5TM232NFBYY-53	
6 Start winding resistance	22.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	17.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.86	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IRAM	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
542	137	159	99	0.51	3.08	5.48	1.38	1.61

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	273	69	80	65	0.36	1.54	4.22	1.06	1.24
-30 (-22)	393	99	115	78	0.42	2.23	5.03	1.27	1.47
-25 (-13)	542	137	159	92	0.48	3.08	5.89	1.48	1.73
-20 (- 4)	720	182	211	106	0.53	4.10	6.79	1.71	1.99
-15 (+ 5)	931	235	273	120	0.59	5.31	7.76	1.96	2.27
-10 (+14)	1175	296	344	134	0.65	6.73	8.81	2.22	2.58

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	228	57	67	67	0.37	1.29	3.44	0.87	1.01
-30 (-22)	339	86	99	79	0.42	1.92	4.29	1.08	1.26
-25 (-13)	481	121	141	94	0.48	2.73	5.13	1.29	1.50
-20 (- 4)	655	165	192	109	0.55	3.73	5.97	1.50	1.75
-15 (+ 5)	863	217	253	126	0.62	4.93	6.83	1.72	2.00
-10 (+14)	1107	279	324	144	0.69	6.34	7.71	1.94	2.26

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	172	43	50	67	0.37	0.97	2.57	0.65	0.75
-30 (-22)	273	69	80	79	0.43	1.55	3.49	0.88	1.02
-25 (-13)	406	102	119	93	0.49	2.30	4.36	1.10	1.28
-20 (- 4)	574	145	168	111	0.56	3.26	5.18	1.31	1.52
-15 (+ 5)	778	196	228	130	0.64	4.44	5.96	1.50	1.75
-10 (+14)	1021	257	299	152	0.73	5.85	6.73	1.70	1.97

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42° up + 24° to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		