

COMPRESSOR DEFINITION

Designation	NE U2183GKA
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	955CA76

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	16.80	[cm ³] (1.025 cu.in)
2.1 Bore [mm]	31.190	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11.2	[kg] (24.69 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	QL2-7.8-NTC-15	
3 Start capacitor	108-130(330)	[µF(VAC minimum)]
4 Run capacitor	17.5(450)	[µF(VAC minimum)]
5 Motor protection	USP-M12-83	
6 Start winding resistance	7.80	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	22.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	3.80	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3271	824	958	637	2.96	22.18	5.14	1.30	1.51

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1512	381	443	374	1.74	10.17	4.03	1.02	1.18
-35	(-31)	2014	507	590	430	1.99	13.58	4.69	1.18	1.37
-30	(-22)	2638	665	773	488	2.25	17.85	5.41	1.36	1.59
-25	(-13)	3386	853	992	548	2.52	23.00	6.18	1.56	1.81
-20	(- 4)	4257	1073	1247	610	2.81	29.07	6.98	1.76	2.04
-15	(+ 5)	5251	1323	1539	674	3.10	36.08	7.79	1.96	2.28
-10	(+14)	6369	1605	1866	739	3.41	44.06	8.61	2.17	2.52

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1332	336	390	376	1.77	8.93	3.55	0.89	1.04
-35	(-31)	1833	462	537	441	2.06	12.33	4.16	1.05	1.22
-30	(-22)	2453	618	719	509	2.37	16.56	4.81	1.21	1.41
-25	(-13)	3193	805	936	581	2.69	21.65	5.48	1.38	1.61
-20	(- 4)	4052	1021	1187	656	3.03	27.62	6.17	1.56	1.81
-15	(+ 5)	5031	1268	1474	734	3.39	34.50	6.86	1.73	2.01
-10	(+14)	6130	1545	1796	816	3.77	42.32	7.52	1.90	2.20

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1161	293	340	368	1.73	7.77	3.15	0.79	0.92
-35	(-31)	1637	413	480	442	2.06	11.00	3.70	0.93	1.09
-30	(-22)	2229	562	653	521	2.41	15.02	4.27	1.08	1.25
-25	(-13)	2937	740	860	605	2.79	19.87	4.85	1.22	1.42
-20	(- 4)	3760	948	1102	694	3.19	25.57	5.43	1.37	1.59
-15	(+ 5)	4700	1184	1377	788	3.62	32.16	5.97	1.51	1.75
-10	(+14)	5756	1450	1687	886	4.07	39.66	6.48	1.63	1.90

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		