

### COMPRESSOR DEFINITION

Designation	ES C+55CBT
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	518102622

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	103 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	103 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	7.87	[cm <sup>3</sup> ] (0.480 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	19.800	
3 Lubricant charge	115	[ml] (3.89 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	5.2	[kg] (11.46 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD2-115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)	[µF(VAC minimum)]
5 Motor protection	4TM302KFBYY-53	
6 Start winding resistance	6.31	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.44	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	8.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.80	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.00	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			GEALBP Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 40.5°C (104.9°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
614	155	180	82	0.77	1.93	7.47	1.88	2.19

### E - PERFORMANCE - CURVES

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal ES/FMS		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 45° up		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 45° up		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		