

COMPRESSOR DEFINITION

Designation	EH X2155U
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513307503

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R290		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	LST/HST - Low/High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	Fan	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	18.4	[kgf/cm ²] (262 psig)	/ °C - °F
9.2 Peak	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	12.21	[cm ³] (0.745 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	23.000	
3 Lubricant charge	270	[ml] (9.13 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO22	
4 Weight (with oil charge)	9.8	[kg] (21.60 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213515054	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM757NFBYY-53	
6 Start winding resistance	14.97	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.67	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	18.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2105	530	617	377	2.24	6.27	5.58	1.41	1.64

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1069	269	313	224	1.70	3.16	4.74	1.20	1.39
-35	(-31)	1358	342	398	252	1.79	4.02	5.39	1.36	1.58
-30	(-22)	1699	428	498	280	1.88	5.04	6.07	1.53	1.78
-25	(-13)	2100	529	615	310	1.98	6.25	6.80	1.71	1.99
-20	(- 4)	2574	649	754	339	2.09	7.68	7.60	1.91	2.23
-15	(+ 5)	3129	788	917	368	2.20	9.37	8.49	2.14	2.49
-10	(+14)	3777	952	1107	396	2.31	11.37	9.51	2.40	2.79

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	960	242	281	228	1.71	2.83	4.24	1.07	1.24
-35	(-31)	1275	321	374	263	1.82	3.77	4.85	1.22	1.42
-30	(-22)	1637	412	480	300	1.94	4.85	5.45	1.37	1.60
-25	(-13)	2054	518	602	338	2.08	6.11	6.07	1.53	1.78
-20	(- 4)	2537	639	743	376	2.23	7.57	6.73	1.70	1.97
-15	(+ 5)	3097	781	908	415	2.39	9.28	7.46	1.88	2.19
-10	(+14)	3745	944	1097	453	2.55	11.27	8.28	2.09	2.43

TEST CONDITIONS: @220V50Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	891	225	261	233	1.74	2.63	3.82	0.96	1.12
-35	(-31)	1211	305	355	274	1.86	3.58	4.41	1.11	1.29
-30	(-22)	1571	396	460	317	2.01	4.66	4.95	1.25	1.45
-25	(-13)	1981	499	580	362	2.18	5.89	5.49	1.38	1.61
-20	(- 4)	2452	618	718	407	2.36	7.31	6.02	1.52	1.77
-15	(+ 5)	2994	755	877	454	2.55	8.97	6.59	1.66	1.93
-10	(+14)	3618	912	1060	501	2.76	10.88	7.22	1.82	2.12

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 40° up + 45° to Back		
3.2 DISCHARGE	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.2 +0.05/+0.05	[mm]	(0.244" +0.002"/+0.002")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		